

Garden City Compost Facility Improvements Construction Drawings for the City of Missoula, Montana





MISSOULA, MT MAP

Missoula Wastewater **Project Area**

FACILITY SITE MAP

WORKSCOPE

Install New Reversing Air Flow Biosolids & Green Waste Composting Facility with Odor Control, Materials Containment and Curing.

FUNDING SOURCES:

State Revolving Fund Loan Program (MDEQ/MDNRC)

DESIGN CRITERIA:

• Design Year: 2044

PROJECT COMPONENTS:

- Excavation and replacement of unsuitable onsite soils with imported engineered fill
- 12-bay aerated compost facility with 2 biofilters
- Primary sensing equipment and automated controls
- Conex control building
- · Concrete biosolids bin



Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Re-Scope

A.Eckhart, P.E. P.Montgomery, P.E. A.Eckhart, P.E.

P.Montgomery, P.E.



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

City Of Missoula

Garden City Compost Facility Improvements

Cover and Project Location

GENERAL	
G-1	Cover
G-2	Sheet Index
G-3	Legend
G-4	Abreviations
G-5	Design Criteria
G-6	Process Flow Diagram
G-7	Geotechnical Borehole Locations
G-8	Location and Survey Control Coordinates
G-9	General Project Notes

INSTRUMENTATION

AND CONTROL

PID-1	PID Symbols and Legend
PID-2	PID Symbols and Legend
PID-3	Compost Area No. 1 & Biofilter No. 1
PID-4	Compost Area No. 2 & Biofilter No. 2
PID-5	Compost Area Network Diagram

SITE DEMOLITION

D-1	Demolition Plan and Photos
D-2	Transitional Facility Demolition Plan and Photos

CIVIL

CIVIL	
C-1	Overall Site Grading Plan
C-2	Site Grading Plan - North
C-3	Site Grading Plan - South
C-4	Site Plan
C-5	Rumble Grate Trough Site Plan
C-6	Curing Site Plan
C-7	Compost Bays and Biofilters Site Plan
C-8	Pre-Compost Containment Bin & Biosolids Bin Site Plan
C-9	Irrigation Well Site Plan
C-10	Plan & Profile - CB-1 to Lift Station
C-11	Plan & Profile - Lift Station to Drying Bed Drain
C-12	Plan & Profile - Biofilter Sump 1 to CB-1
C-13	Plan & Profile - Biofilter Sump 2 to CB-3
C-14	Plan & Profile - Sump 2 to Runoff Lift Station
C-15	Plan & Profile - E-One LS to LS Forcemain
C-16	Runoff Control Plan

CIVIL DETAILS

CD-1	Civil Details
CD-2	Civil Details
CD-3	Civil Details
CD-4	Pipe Supports
CD-5	Manhole Details
CD-6	Catch Basin 1 Details
CD-7	Catch Basin 2 Details
CD-8	Catch Basin 3 Details
CD-9	Lift Station Plan
CD-10	Lift Station Section
CD-11	E-One Lift Station Details
CD-12	Irrigation Well Details
CD-13	Irrigation Plumbing Diagram

CONTROL BUILDING

CB-1	Control Building Plan
CB-2	Control Building North & South Elevations
CB-3	Control Building East & West Elevations
CB-4	Control Building Anchors

M-1	Compost Bays Piping Plan
M-2	Compost Bay Piping Details
M-3	Compost Bay Aeration Piping Details
M-4	Compost Bay Aeration Sections
M-5	Biofilter Bays Piping
M-6	Biofilter 1 Details
M-7	Biofilter 1 Piping Details
M-8	Biofilter Details

MECHANICAL

M-9

M-10	Biofilter 2 Details
M-11	Biofilter 2 Piping Details
M-12	Biofilter 2 Condensate Collection Details
M-13	Biofilter 1 Condensate Sump 1 Details
M-14	Biofilter 2 Condensate Sump 2 Details
M-15	Compost Condensate Collection
M-16	Compost Condensate Collection Section
M-17	Compost Condensate Sump 1 Details
M-18	Foul Air to Biofilter Condensate Collection
M-19	Foul Air to Biofilter Condensate Collection

M-19	Foul Air to Biofilter Condensate Collection Section
M-20	Condensate Sump 2 Details
M-21	Biofilter 1 Condensate Cleanout Details
M-22	Biofilter 2 Condensate Cleanout Details

Biofilter 1 Condensate Collection Details

IVI-ZZ	biolitter 2 Condensate Cleano
M-23	Biofilter Bays Irrigation
M-24	Curing Bays

141 2 1	curing buys
M-25	Curing Bays Sections
M-26	Curing Bays Section & Details
M-27	Curing Blower & Control Shed Details

171-27	curing blower & control s
M-28	Curing Blower Details
M-29	Mechanical Details

IVI-3U	instrument De

STRUCTURAL

S-1	Structural Notes
S-2	Structural Notes Continued
S-3	Structural Details
S-4	Structural Details
S-5	Structural Details
S-6	Structural Details
S-7	Structural Details
S-8	Structural Details
S-9	Overall Slab On Grade Plan
S-10	Compost Bays Plan
S-11	Biofilters Plan
S-12	Push Wall Sections
S-13	Biosolids Bin Details
S-14	Pre-Compost Containment Bin Details
S-15	Biosolids Bin Wall Elevations
S-16	Biosolids Bin Details
S-17	Curing Wall Details
S-18	Rumble Grate Trough
S-19	Rumble Grate Trough Details

ELECTRICAL

E-0	Schedules and Legend
E-1	Overall Electrical Site Plan
E-2	One-Line Diagram
E-3	Control Building Electrical Plans
E-4	Compost and Biofilter Electrical Plan

DRAWING IDENTIFICATION SYSTEM:

LETTER	DISCIPLINE
G	GENERAL
PID	INSTRUMENTATION AND CONTROL
D	SITE DEMOLITION
С	CIVIL
CD	CIVIL DETAILS
СВ	CONTROL BUILDING
М	MECHANICAL
S	STRUCTURAL
Е	ELECTRICAL

DETAIL DESIGNATION:

A D C C IS

— DETAIL OR SECTION DESIGNATION

ON DWG WHERE SECTION OR DETAIL
IS TAKEN: DWG NO. WHERE SHOWN
ON DWG WHERE SECTION OR DETAIL

ON DWG WHERE SECTION OR DETAIL IS SHOWN: DWG NO. WHERE TAKEN

EMPRIL MARKET	
Exan	7
3265- Jan O	

	Revision	Date	Ву
	Final	4/2/25	AE
	Re-Scope	5/7/25	AE

Revision Re-Scope
Plot Scale
1:2
Drawn By
A.Eckhart, P.E.
Approved By
P.Montgomery, P.E.

A.Eckhart, F.E.
Approved By
P.Montgomery, P.E.
Checked By
A.Eckhart, P.E.
Designed By
P.Montgomery, P.E.

Engineer



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Owner

City Of Missoula


Project Title

Garden City Compost Facility Improvements

Sheet Title

Index

Sheet



VALVE SYMBOLS						
DOUBLE LINE	SINGLE LINE	DESCRIPTION	DOUBLE LINE	SINGLE LINE	DESCRIPTION	
	—> —	GLOBE		<u> </u>	SAMPLE VALVE NO THREAD OUTLET	
E		GATE		*	HOSE VALVE	
2 × 3	->>-	BALL		x D —	NON FREEZE HOSE VALVE, X=NO IN SPECS	
		PLUG		x	NON FREEZE HOSE VALVE, X=NO IN SPECS	
		BUTTERFLY		S	SAMPLE	
2 X		DIAPHRAGM			PRESSURE RELIEF	
	->>-	PINCH			SURGE CONTROL	
	-	SWING CHECK		个	AIR/VACUUM	
EK B	-K-	DOUBLE DISK CHECK		À	REGULATED SIDE PRESSURE REDUCING	
26 B	─ \\	BALL CHECK		À	PRESSURE REDUCING VALVE	
	_ _	AIR DAMPER		×	FLOW CONTROL VALVE / NEEDLE VALVE	

DESCRIPTION	SINGLE LINE	DOUBLE LINE	DESCRIPTION	SINGLE LINE	DOUBLE LINE		
CONCRETE	4 1 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4		CABLE TV -	TV	TV —		
GRAVEL			CURB =				
PAVEMENT			DRAINAGE DITCH		· · · · · ·		
CURB AND SIDEWALK			ROAD				
PROPERTY LINE -			BUILDING				
EASEMENT			DROP INLET	—	■-		
RIGHT OF WAY			EASEMENT PIN	•	•		
GRAVEL ROAD			POWER POLE	•	•		
CONTOURS	4200	4200	POWER POLE WITH GUY WIRE		•		
DRAINAGE			LIGHT POLE	•-*	•*		
WATER	为 12"W	₩ ₩	SURVEY POINT				
WATER SERVICE LINE			CONTROL POINT	<u></u> СР	ДСР		
WATER SERVICE	us.		TELEPHONE PED	□ PED	□ PED		
SANITARY SEWER		SS S	TELEPHONE BOX	п	п		
STORM DRAIN	========		ELECTRICAL BOX				
FENCE LINE (BARB WIRE)	o o o	· · · · · · · · · · · · · · · · · · ·	CURB BOX, SIGN	0	0		
FENCE LINE (CHAIN LINK)	× × ×	× × ×	DRILL HOLE OR TEST PIT	● DH1 TP1	● DH1 TP1		
SIGN	- 	-o- - o-o-	CATTLE GUARD				
OVERHEAD POWER	OHPWR —		SECTION CORNER	*	*		
JNDERGROUND FIBER OPTIC	FO		QUARTER CORNER	++	++		
UNDERGROUND ELEPHONE, PEDESTAL	PH		FROST FREE HYDRANT		Ō		
UNDERGROUND GAS -	GAS		HOSE BIB		(HB)		
UNDERGROUND POWER, TRANSFORMER	T PWR		FROST FREE HOSE BIB		(FF HB)		
NATURAL GAS			NOTES: CONTACT THE E	NGINEER FOR SYI	MBOLS NOT LIST		
HOT WATER			THIS IS A STANDARD LEGEND SHEET. THEREFC SOME SYMBOLS MAY APPEAR ON THIS SHEET A MAY NOT BE UTILIZED ON THIS PROJECT.				
COLD WATER			IVIAT NOT BE UT	LIZED ON THIS PR	OJECT.		
NON-POTABLE WATER							
PLANT AIR							



Revision	Date	By
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Revision
Re-Scope
Plot Scale
1:2
Drawn By
A.Eckhart, P.E.

A.Eckhart, P.E.
Approved By
P.Montgomery, P.E.
Checked By
A.Eckhart, P.E.
Designed By
P.Montgomery, P.E.

Engineer



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Owner

City Of Missoula

Project Title

Garden City Compost Facility Improvements

Sheet Title

Legend

Sheet

		A	ABBREVIATIONS:		
Ø AA AB AC AFF ADA AH AL ANC ANSI APPROX ARV AVE AWWA	DIAMETER AT ALL AROUND ANCHOR BOLT, AGGREGATE BASE ASBESTOS CEMENT OR ACRE ABOVE FINISHED FLOOR AMERICANS WITH DISABILITIES ACT AHEAD ALUMINUM ANCHOR AMERICAN NATIONAL STANDARDS INSTITUTE APPROXIMATELY AIR RELEASE VALVE AVENUE AMERICAN WATER WORKS ASSOCIATION	FG FH FL FOC FM FPT FS FTG FT G GA GALV GPD GPM GPS	FINISH GRADE FIRE HYDRANT FLOOR, FLANGE OR FLOW LINE FACE OF CURB OR FACE OF CONCRETE FORCE MAIN FEMALE PIPE THREAD FINISHED SURFACE FOOTING FOOT OR FEET GAS GAUGE GALVANIZED GALLONS PER MINUTE	R RCB RCPA RDCR RFC ROW RPA RPC RPC RRF RR RT RW R/W RWL	RADIUS REINFORCED CONCRETE BOX REINFORCED CONCRETE PIPE REINFORCED CONCRETE PIPE ARCHED REDUCER ROTATED FOR CLARITY RIGHT—OF—WAY ROBERT PECCIA & ASSOCIATES RED PLASTIC CAP REINFORCED POLYPROPYLENE RAILROAD RIGHT RIGHT—OF—WAY OR RACEWAY RIGHT—OF—WAY RAIN WATER LEADER
BC BF BFF BFV BGS BK BLDG BLVD BM BOC BOD BV BVC	BUILDING CORNER BLIND FLANGE BELOW FINISH FLOOR BUTTERFLY VALVE BELOW GROUND SURFACE BACK BUILDING BOULEVARD BENCH MARK BACK OF CURB BIOCHEMICAL OXYGEN DEMAND BALL VALVE BEGIN VERTICAL CURVE	GSP GV GW HD HDPE HDR HGT HP HT HWY HYD	GLOBAL POSITIONING SYSTEM, GALLONS PER SECOND GALVANIZED STEEL PIPE GATE VALVE GREEN WASTE HEAVY DUTY OR HOT-DIPPED HIGH DENSITY POLYETHYLENE PIPE HEADER HEIGHT HORSEPOWER HEIGHT HIGHWAY HYDRANT INSTRUMENTATION & CONTROL	S SBB S/C SCH SDI SDR SEB SECT SF SIM SQFT SS SSSMH	SLOPE SLUDGE BUFFER BASINS SERVICE CONNECTION SCHEDULE STORM DRAIN STORM DRAIN INLET STANDARD DIMENSION RATIO SMALL END BELL SECTION SQUARE FOOT/FEET SIMILAR SQUARE FOOT/FEET SANITARY SEWER MANHOLE
C CARV CATV CF CFS CI CIP	CHANNEL OR CENTER COMBINATION AIR RELEASE VALVE CABLE TELEVISION CUBIC FEET CUBIC FEET PER SECOND CAST IRON OR CURB INLET CAST IRON PIPE OR CAST—IN—PLACE	IBC IBC ID IN INFL INT INV	INSTRUMENTATION & CONTROL INTERNATIONAL BUILDING CODE INSIDE DIAMETER INCH INFLUENT INTERIOR OR INTERSECTION INVERT	SSP ST STA STD STL SUPER SY	SPIRAL STEEL PIPE STREET STATION STANDARD STEEL OR STEEL PIPE SUPERNATENT SQUARE YARDS
CIPP CL CLR CMP CMU CO CONC COS CP CPE CPLG CPVC CSP CV	CURED—IN—PLACE PIPE CENTERLINE CLEAR CORRUGATED METAL PIPE CONCRETE MASONRY UNIT CLEANOUT CONCRETE CERTIFICATE OF SURVEY CONTROL POINT CORRUGATED POLYETHYLENE PIPE COUPLING CHLORINATED POLYVINYL CHLORIDE CORRUGATED STEEL PIPE CHECK VALVE	K KW L LB(S) LD LEB LF LT LS MAX MC	KILOMETER KILOWATT ANGLE, LONG POUND(S) LOCAL DISCONNECT LARGE END BELL LINEAL FOOT OR LINEAR FEET LEFT LIFT STATION MAXIMUM MECHANICAL COUPLING	T TBC TBLAY TBM TDW TEMP THD TOA TOC TOG TOS TOW TTS	TELEPHONE TOP BACK OF CURB TOP BACK OF LAYDOWN CURB TEMPORARY BENCH MARK TREATED DISINFECTED WATER TEMPERATURE OR TEMPORARY THREAD TOP OF ASPHALT TOP OF CONCRETE TOP OF GRATE TOP OF SIDEWALK TOP OF WALL TEST PIT TECHNICAL SPECIFICATIONS
CY C1D1 CB DEC DEMO DEPT DH DI DI	CUBIC YARDS CLASS 1 DIVISION 1 CATCH BASIN DECANT DEMOLISH DEPARTMENT DRILL HOLE (SOIL BORING) DUCTILE IRON OR DRAIN INLET DIAMETER	MCC MDT MECH MFR MH MIN MJ MPT MPWSS	MOTOR CONTROL CENTER MONTANA DEPT. OF TRANSPORTATION MECHANICAL MANUFACTURER MANHOLE MINIMUM OR MINUTE MECHANICAL JOINT MALE PIPE THREAD MONTANA PUBLIC WORKS STANDARD SPECIFICATIONS	TV TW TWAS TYP UBC UG UGP UPC	CABLE TELEVISION TREATED WATER THICKENED WASTE ACTIVATED SLUDGE TYPICAL UNIFORM BUILDING CODE UNDERGROUND UNDERGROUND POWER UNIFORM PLUMBING CODE
DIMJ DIP DL DR DWAS DWG	DUCTILE IRON MECHANICAL JOINT DUCTILE IRON PIPE DRAIN LINE DRAIN OR DIMENSION RATIO DIGESTED WASTE ACTIVATED SLUDGE DRAWING EACH	MTL MWS N NEC N.I.C. NO. NPT NPW	MATERIAL MAXIMUM WATER SURFACE NORTH NATIONAL ELECTRICAL CODE NOT IN CONTRACT NUMBER NATIONAL PIPE THREAD NON—POTABLE WATER	V VERT VFA VLV VPC VPT VTR	VENT, VOLT OR VALVE VERTICAL VOLATILE FATTY ACID VALVE VERTICAL POINT OF CURVATURE VERTICAL POINT OF TANGENCY VENT THROUGH ROOF
EFF ELEV EOC EOP EOS EPDM EVC EW EXT EXIST	EFFLUENT ELEVATION EDGE OF CONCRETE EDGE OF PAVEMENT EDGE OF SIDEWALK ETHYLENE PROPYLENE DIENE M—CLASS RUBBER END VERTICAL CURVE EACH WAY EXTERIOR EXISTING	OAL OC OD OF OHP	OVERALL LENGTH ON CENTER OUTSIDE DIAMETER OUTSIDE FACE OR OVERFLOW OVERHEAD POWER POINT OF CURVATURE PLAIN END PHONE	- W W/O WAS WLC WS - WSO WSP WV	WATER OR WEST WITH WITHOUT WASTE ACTIVATED SLUDGE WATER LEVEL CONTROL WATER SURFACE OR WATER STOP WATER SERVICE OUTLET WELDED STEEL PIPE WATER VALVE WASTEWATER
FAB FC FCA FDN FETS FF	FABRICATION FLEXIBLE COUPLING FLANGED COUPLING ADAPTER FOUNDATION FLARED END TERMINAL SECTION FINISHED FLOOR FOUL AIR	PI PL PLCS PROP PSI PSIG PT PVC PVI PWR	POINT OF INTERSECTION PROPERTY LINE OR PLATE PLACES PROPERTY OR PROPOSED POUNDS PER SQUARE INCH POUNDS PER SQUARE INCH, GAUGE POINT OF TANGENCY POLYVINYL CHLORIDE PLASTIC POINT OF VERTICAL INTERSECTION POWER	X XING YD YPC	WELDED WIRE FABRIC USED AS A VARIABLE CROSSING YARD YELLOW PLASTIC CAP

- NOTES:
 CONTACT THE ENGINEER FOR ABBREVIATIONS NOT LISTED.
 THIS IS A STANDARD ABBREVIATIONS SHEET. THEREFORE, SOME ABBREVIATIONS MAY APPEAR ON THIS SHEET AND MAY NOT BE UTILIZED ON THIS PROJECT.



	Revision	Date	Ву
	Final	4/2/25	AE
	Re-Scope	5/7/25	AE

Revision
Re-Scope
Plot Scale
1:2
Drawn By
A.Eckhart, P.E.

A.Eckhart, P.E.
Approved By
P.Montgomery, P.E.
Checked By
A.Eckhart, P.E.
Designed By
P.Montgomery, P.E.



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

City Of Missoula

Project Title

Garden City Compost Facility Improvements

Sheet Title

Abbreviations

Design Year		2044	
Description	<u>Parameter</u>	Units	Design Valu
Materials			
	Calendar Days	Dry Tons/Day	7.3
Biosolids Quantity	5 Day/Week Operating Days	Dry Tons/Day	10.2
Diosolius Quartity	Calendar Days	Wet Tons/Day	47
	5 Day/Week Operating Days	Wet Tons/Day	66
	Solids Content	% Total Solids	15.5
Biosolids Characteristics	Volatile Solids	% Volatile Solids	80
	Bulk Density	Pounds/Cubic Yard	1600
Now Pulking Agent	Solids Content	% Total Solids	65
New Bulking Agent	Bulk Density	Pounds/Cubic Yard	450
Compost	Solids Content	% Total Solids	60
Compost	Bulk Density	Pounds/Cubic Yard	900
Mixing			
Batch Mixer	Operational Schedule	Hours/Day (5 Day Operations)	4
Composting			
la lati a I Mila a Ola a una ata anta ata a	Solids Content	% Total Solids	40
nitial Mix Characteristics	Bulk Density	Pounds/Cubic Yard	880
Data ati an Tima	Calendar Days		21
Detention Time	Working Weeks		3
	Base Depth	Feet	1
Dille Discounting	Mix Height	Feet	10
Pile Dimensions	Cover Height	Feet	1
	Total Height	Feet	12
	Method	Positive or Negative	Negative
Aeration	Capacity	Cubic Feet Per Hour/Dry Ton	5000


Description	Parameter	Units	Design Value
Screening	<u>Parameter</u>	Onits	Design value
Portable Screen	T ,		
Screen Type	Trommel		Trommel
Screen Size		Inches	3/8
Feed Capacity		Cubic Yards/Hour	>50
Redundant Unit			Yes
Curing			
Detention Time	Calendar Days		30
Determon time	Working Days		4
	Base Depth	Feet	0
Dila Dimanajana	Mix Height	Feet	10
Pile Dimensions	Cover Height	Feet	0
	Total Height	Feet	10
	Method	Positive or Negative	Positive
Aeration	Capacity	Cubic Feet Per Hour/Dry Ton	1200
Storage			
Biosolids Receiving Bunker		Operational Days	0.5
Bulking Agent Uncovered 10'		Operational Days	20
Recycled Bulking Agent Uncovered		Operational Days	1
Compost Product Uncovered		Calendar Days	90
Odor Control			
Compost Process Exhaust		Continuous	Yes
Biofilter Dilution Air Ratio		% Dilution Air	300
Biofilter Empty Bed Contact Time		Seconds	60
Biofilter Depth		Feet	6

BASE BID

- Excavation of unsuitable materials and engineered structural backfill within compost facility footprint
- 12-Bay, reversing airflow composting facility concrete back wall and slab; in-floor aeration; runoff collection; condensate collection; blowers; dampers; fittings
- Two Biofilters, above ground air delivery; condensate collection; blowers; dampers; fittings; irrigation system; groundwater well & controls
- Conex Control Building complete compost control system; primary sensing devices; HMI; motor controls; electrical; HVAC
- Runoff Lift Station submersible pump station to deliver contact runoff to the POTW drying bed drain to headworks
- Biosolids Bin concrete walls and slabs
- Pre-Compost Bin concrete slab

ADDITIVE ALTERNATE A

Concrete working apron



Revision
Re-Scope
Plot Scale
1:2
Drawn By
A.Eckhart, P.E.
Approved By
P.Montgomery, P.E.
Checked By
A.Eckhart, P.E.
Designed By
P.Montgomery, P.E.

Engineer



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Ouman

City Of Missoula


Project Title

Garden City Compost Facility Improvements

Sheet Title

Design Criteria

She





Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Revision Re-Scope

1:2

A.Eckhart, P.E.

Approved By
P.Montgomery, P.E.

Checked By

Checked By
A.Eckhart, P.E.
Designed By
P.Montgomery, P.E.

Engineer



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Owner

City Of Missoula

Project Title

Garden City Compost Facility Improvements

Sheet Title

Compost Facility Process Flow Diagram

She

NOTES:
GEOTECHNICAL REPORT INCLUDED IN APPENDIX C OF THE CONTRACT DOCUMENTS.





- 1 BOREHOLES TP-01 TEST PITS TP-01 TEST PITS

	Revision	Date	Ву
	Final	4/2/25	AE
	Re-Scope	5/7/25	AE

Re-Scope

Drawn By
A.Eckhart, P.E.
Approved By
P.Montgomery, P.E.
Checked By
A.Eckhart, P.E.
Designed By
P.Montgomery, P.E.



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

City Of Missoula

Garden City Compost Facility Improvements

Geotechnical Borehole Locations

G-7

Borehole Locations

SURVEY CONTROL

MODIFIED STATE PLANE COORDINATES (FEET) - MONTANA 2500

SCALED TO GROUND AT POINT 304

BY SCALE FACTOR 1.000753

POINT	NORTHING	EASTING	ELEVATION	DESCRIPTION
51	992140.92	832940.71	3152.54	SET NAIL
52	992149.79	832505.60	3150.12	SET NAIL
53	991736.00	832459.36	3149.07	SET NAIL
54	991748.41	832257.95	3149.68	SET NAIL
55	991065.16	832028.04	3148.66	SET NAIL
56	991013.85	832370.54	3149.29	SET NAIL
57	991284.01	832617.67	3146.53	SET NAIL
58	991215.96	833419.67	3156.32	SET NAIL
59	991767.05	833415.70	3155.14	SET MAG NAIL IN CONCRETE
60	991947.37	833543.61	3152.64	SET MAG NAIL IN ASPHALT
61	992124.10	833471.77	3152.77	SET MAG NAIL IN ASPHALT
304	992117.08	833477.74	3152.23	FOUND 1 ½" ALUMINUM CAP (AINSWORTH 2923S)

1/4	SEC	Т	R
X	18	13N	19W
PRINCIPA	AL MERID	IAN OF M	IONTANA
	CITY OF M	1ISSOUL <i>A</i>	4
MISSO	ULA COU	NTY, MO	NTANA

BASIS OF BEARINGS
GRID NORTH OF MONTANA STATE
PLANE COORDINATE SYSTEM (FIPS 2500) NAD83 (2011) (EPOCH 2010.00) (GROUND DISTANCES SHOWN)

VERTICAL DATUM NAVD 1988 MSOL CORS

SURVEY TIMELINE
INITIAL SURVEY DATE: MAY 9, 2024
PLOT DATE: JUNE 14, 2024

NOTE:

Awarded Contractor will be provided with the AutoCAD file for survey & locating purposes. Contractor will be responsible for accurately locating all new facility improvements.





	_	
Revision	Date	By
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Re-Scope 1:2

Drawn By
A.Eckhart, P.E. Approved By
P.Montgomery, P.E. Checked By
A.Eckhart, P.E.
Designed By
P.Montgomery, P.E.



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

City Of Missoula

Project Title

Garden City Compost Facility Improvements

Location and Survey Control Coordinates

G-8

Location and Survey Control Coordinates

GENERAL NOTES:

- 1. CONTRACTOR TO OBTAIN ALL REQUIRED PERMITS FOR CONSTRUCTION, DEWATERING AND STORMWATER DISCHARGES.
- 2. AS CONSTRUCTED ELEVATIONS SHALL BE WITHIN 0.08' OF ELEVATION SPECIFIED ON THE PLAN DRAWINGS.
- 3. CONTRACTOR SHALL PROTECT AND PRESERVE ALL EXISTING SITE FEATURES (INCLUDING VEGETATION, SURFACES, STRUCTURES, SURVEY MONUMENTATION, ETC.) TO THE GREATEST EXTENT POSSIBLE DURING CONSTRUCTION. ANY DAMAGE TO EXISTING SITE FEATURES SHALL BE REPAIRED TO ORIGINAL OR BETTER CONDITION AT NO ADDITIONAL COST TO THE OWNER.
- 4. CONTRACTOR SHALL BE RESPONSIBLE FOR DETERMINING SEWER MAIN SIZE, MATERIAL TYPE, MANHOLE SIZE, MATERIALS AND CONDITION PRIOR TO INITIATION OF SEWER SYSTEM WORK.
- 5. CONTRACTOR SHALL BE RESPONSIBLE FOR PROPER DUST CONTROL DURING CONSTRUCTION.
- 6. CONTRACTOR MUST COMPLY WITH CITY OF MISSOULA REQUIREMENTS FOR CONSTRUCTION CONTRACTORS. SEE SPECIAL PROVISIONS

NOTES FOR WATER AND SEWER MAINS:

- 1. THE OWNER AND RESIDENTS SHALL BE NOTIFIED PRIOR TO CHANGE OR DISRUPTION OF WATER OR SEWER SYSTEM OPERATION.
- 2. AERATION PIPING SHALL BE BUTT-FUSED HDPE DR17 UNLESS SPECIFICALLY CALLED OUT OTHERWISE IN THE PROJECT DRAWINGS.
- 3. SEWER MAIN PIPING SHALL BE DUCTILE IRON OR SDR-35 PVC SEWER PIPE.
- 4. ALL WATERMAIN AND FORCEMAIN FITTINGS, INCLUDING WYES, REDUCERS AND ELBOWS EQUAL TO OR GREATER THAN 22-1/2° SHALL BE RESTRAINED MECHANICAL JOINT. ALL MECHANICAL JOINT RESTRAINTS SHALL BE "MEGALUG". UNIFLANGE OR EQUAL. JOINT RESTRAINT SHALL BE IN ADDITION TO MEETING THRUST BLOCK REQUIREMENTS IN ACCORDANCE WITH THE PROJECT SPECIFICATIONS AND MPW STANDARD DRAWINGS 02660-1 AND 02660-3
- 5. TRENCHES FOR THE INSTALLATION OF WATER MAINS AND SEWER MAINS SHALL BE PROPERLY BACKFILLED AS QUICKLY AS POSSIBLE, BUT NO MORE THAT 48-HOURS AFTER INITIAL DIGGING.
- 6. WHEN WORKING NEAR AND/OR EXPOSING EXISTING UTILITIES AND SERVICE LINES, WORKERS SHALL UTILIZE HAND-DIGGING IN ORDER TO AVOID DAMAGE TO THOSE UTILITIES. IF DAMAGE OCCURS, THE COST OF REPAIR AND PENALTIES SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR

UTILITY NOTES:

- 1. THE ENGINEER HAS OBTAINED UNDERGROUND UTILITY INFORMATION FROM OWNERS OF THE UNDERGROUND FACILITIES AND INCLUDED THAT INFORMATION AS PART OF THESE PLANS. THIS UTILITY LOCATION INFORMATION IS APPROXIMATE AND MAY BE INCOMPLETE.
- 2. BEFORE BEGINNING AN EXCAVATION, THE CONTRACTOR SHALL NOTIFY, THROUGH ONE-CALL NOTIFICATION CENTER, ALL OWNERS OF UNDERGROUND FACILITIES IN THE AREA OF THE PROPOSED EXCAVATION. THE PHONE NUMBER IS: 1-800-424-5555 OR 811. WEBSITE: WWW.CALLBEFOREYOUDIG.ORG
- 3. AFTER AN OWNER OF AN UNDERGROUND FACILITY HAS LOCATED AND MARKED THE UNDERGROUND FACILITIES. THE CONTRACTOR SHALL DETERMINE IF WEATHER, TIME, OR OTHER FACTORS MAY HAVE AFFECTED LOCATION MARKS, WARRANTING RELOCATION OF THE FACILITIES
- 4. IF EXCAVATION HAS NOT OCCURRED WITHIN 30 DAYS OF THE LOCATE AND MARK, THE CONTRACTOR SHALL REQUEST THAT THE FACILITY BE RELOCATED AND REMARKED BEFORE EXCAVATING UNLESS OTHER ARRANGEMENTS HAVE BEEN MADE WITH THE UNDERGROUND FACILITY OWNER. THE CONTRACTOR IS RESPONSIBLE FOR ALL COSTS ASSOCIATED WITH RELOCATING AND REMARKING A FACILITY THAT IS NOT EXCAVATED WITHIN 30 DAYS OF THE LOCATE AND MARK.
- 5 THE CONTRACTOR MAY NOT BEGIN EXCAVATING REFORE THE LOCATING AND MARKING IS COMPLETE OR BEFORE THE CONTRACTOR IS NOTIFIED THAT LOCATING AND MARKING IS UNNECESSARY.
- 6. THE CONTRACTOR SHALL LOCATE AND MARK THE AREA TO BE EXCAVATED IF REQUESTED BY THE UNDERGROUND FACILITY OWNER OR THEIR REPRESENTATIVE. IF THE CONTRACTOR DISCOVERS AN UNDERGROUND FACILITY THAT HAS NOT BEEN LOCATED AND MARKED, THE CONTRACTOR SHALL STOP EXCAVATING IN THE VICINITY OF THE FACILITY AND NOTIFY THE FACILITY OWNER OR THE ONE-CALL NOTIFICATION CENTER. IF THIS OCCURS THE CONTRACTOR SHALL PROCEED WITH OTHER ELEMENTS OF THE PROJECT, AT NO COST TO THE PROJECT OWNER, UNTIL THE UNDERGROUND FACILITY OWNER HAS NOTIFIED THE CONTRACTOR THAT EXCAVATION CAN PROCEED.



	Revision	Date	Ву
	Final	4/2/25	AE
	Re-Scope	5/7/25	AE

Re-Scope	5/7/25	AE
Revision		

Re-Scope

1:2
Drawn By
A.Eckhart, P.E.
Approved By
P.Montgomery, P.E
Checked By
A.Eckhart, P.E.
Designed By

P.Montgomery, P.E.

Plot Scale



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

City Of Missoula

Project Title

Garden City Compost Facility Improvements

Sheet Title

General Project Notes

INSTRUMENT IDENTIFICATION

EXAMPLE SYMBOLS

FIRST LETTER (S) SUCCEEDING LETTERS THE TOTAL NUMBER OF UNITS PER SET (Y VARIES FROM 1 TO A) THE TOTAL NUMBER OF SETS OF UNITS (Z VARIES FROM 1 TO B) XXX

LOOP NUMBER

<u>(π</u>)

FIELD MOUNTED INSTRUMENT

FY JI/F

REAR-OF-PANEL MOUNTED INSTRUMENT

FIC

PANEL MOUNTED INSTRUMENT



MOTOR CONTROL CENTER MOUNTED INSTRUMENT

SPECIAL CASES

QL OO

ON AND OFF EVENT LIGHTS



OPENED AND CLOSED POSITION LIGHTS



OPENED AND CLOSED POSITION SWITCHES



ON-OFF HAND SWITCH MAINTAINED CONTACT SWITCH (CONTROLLED DEVICE WILL RESTART ON RETURN OF POWER AFTER POWER FAILURE).



STOP-START HAND SWITCH MOMENTARY CONTACT SWITCHES (CONTROLLED DEVICE WILL NOT RESTART ON RETURN OF POWER AFTER POWER FAILURE).

ELECTRIC ACTUATOR WITH INTEGRAL OPEN-STOP-CLOSE



FLOW INDICATING, COMPUTER/MANUAL CONTROL



FLOW INDICATING, COMPUTER/AUTO/MANUAL CONTROL STATION

MOMENTARY CONTACT CONTROL SWITCH



FLOW INDICATING SUPERVISORY SET POINT (BY COMPUTER), AUTO/MANUAL CONTROL STATION

INSTRUMENT SOCIETY OF AMERICA TABLE

	FIRST LETTER (S)		SUCCEEDING L	SUCCEEDING LETTERS		
LETTER	PROCESS OR INITIATING VARIABLE	MODIFIER	READOUT OR PASSIVE FUNCTION	OUTPUT FUNCTION	MODIFIER	
Α	ANALYSIS (+)		ALARM			
В	BURNER FLAME		USERS CHOICE (+)	USERS CHOICE (+)	USERS CHOICE (+)	
С	CONDUCTIVITY			CONTROL		
D	DENSITY (S.G)	DIFFERENTIAL				
E	VOLTAGE		PRIMARY ELEMENT			
F	FLOW RATE	RATIO				
G	GAUGE		GLASS	GATE		
Н	HAND (MANUAL)				HIGH	
1	CURRENT		INDICATE			
J	POWER	SCAN				
K	TIME OR SCHEDULE			CONTROL STATION		
L	LEVEL		LIGHT (PILOT)		LOW	
M	MOTION				MIDDLE	
N	USERS CHOICE (+)		USERS CHOICE (+)	USERS CHOICE (+)	USERS CHOICE (+)	
0	USERS CHOICE (+)		ORIFICE			
Р	PRESSURE (OR VACUUM)		POINT (TEST CONNECTION)			
Q	QUANTITY OR EVENT(+)	INTEGRATE	INTEGRATE			
R			RECORD OR PRINT			
S	SPEED OR FREQUENCY	SAFETY		SWITCH		
Т	TEMPERATURE			TRANSMIT		
U	MULTIVARIABLE (+)		MULTIFUNCTION (+)	MULTIFUNCTION (+)	MULTIFUNCTION (+)	
V	VISCOSITY			VALVE OR DAMPER		
W	WEIGHT OR FORCE		WELL			
X	UNCLASSIFIED (+)		UNCLASSIFIED (+)	UNCLASSIFIED (+)	UNCLASSIFIED (+)	
Y	USERS CHOICE (+)			RELAY OR COMPUTE (+)		
Z	POSITION			DRIVE, ACTUATE OR UNCLASSIFIED FINAL CONTROL ELEMENT		

(+) WHEN USED, EXPLANATION IS SHOWN ADJACENT TO INSTRUMENT SYMBOL. SEE ABBREVIATIONS AND LETTER SYMBOLS.



COMPLITER ACCESSIBLE TO THE OPERATER



PROGRAMMABLE LOGIC CONTROLLER



PROGRAMMABLE LOGIC CONTROLLER, INPUT/OUTPUT (!/O) X=TOTAL NUMBER OF INPUT/OUTPUT POINTS



TRANSDUCERS

Α	ANALOG	1	CURRENT
D	DIGITAL	Р	PNEUMATIC
E	VOLTAGE	PF	PULSE FREQUENCY
F	FREQUENCY	PD	PULSE DURATION
Н	HYDRAULIC	R	RESISTANCE


EXAMPLE:




CURRENT TO PNEUMATIC TRANSDUCER (BACK OF PANEL, IN A FLOW LOOP)

LINE LEGEND


PROCESS (CLOSED CONDUIT. DASHED LINE INDICATES ALTERNATE FLOW STREAM)















INTERFACE SYMBOLS



∫ A D

= PROCESS INTERFACE = INTERFACE LETTER

= DESTINATION DRAWING NO. = SOURCE DRAWING NO

PROCESS OR SIGNAL LINE CONTINUATION N=1,2,3,ETC



ANALOG INPUT TO CONTROLLER


DISCRETE INPUT TO **PROGRAMMABLE** CONTROLLER



ANALOG OUTPUT FROM PROGRAMMABLE CONTROLLER DISCRETE OUTPUT FROM PROGRAMMABLE

ABBREVIATIONS & LETTER SYMBOLS

AC	ALTERNATING CURRENT	
ACK	ACKNOWLEDGE ALARM	
ALKY	ALKALINITY	
AM	AUTO-MANUAL	
	COMPUTER-AUTO-MANUAL	
CCS	CENTRAL CONTROL SYSTEM	
CL ₂ etc.	CHLORINE (TYPICAL: USE STANDARD CHEMICAL	
2	ELEMENT ABBREVIATION)	
CM	COMPUTER-MANUAL	
COD	CHEMICAL OXYGEN DEMAND	
CP-X	CONTROL PANEL NO. X	
DC	DIRECT CURRENT	
	DISSOLVED OXYGEN	
D		
FA	FOUL AIR	
FCL ₂	FREE CHLORINE RESIDUAL FAST-OFF-SLOW	
FOS	FAST-OFF-SLOW	
FOSA	FAST-OFF-SLOW-AUTO	
FOSR	FAST-OFF-SLOW-REMOTE	
FP-W-X	FIELD PANEL NO. WX (W = UNIT PROCESS NUMBER	
	X = PANEL NUMBER)	
	FORWARD-REVERSE	
	HARDNESS	
HOA	HAND-OFF-AUTO	
HOR	HAND-OFF-REMOTE	
LEL	LOWER EXPLOSIVE LIMIT	
LOS	LOCKOUT STOP	
LR	LOCAL-REMOTE	
	MANUAL-AUTO	
MBAS	METHYLENE BLUE ACTIVE SUBSTANCES	
MC	MODULATE-CLOSE	
MCC-X	MOTOR CONTROL CENTER NO. X	
OC		
OCR	OPEN-CLOSE-REMOTE	



RTU-X REMOTE TELEMETRY UNIT NO. X SF SLOWER-FASTER START-STOP

SS SSC SUPERVISORY SET POINT CONTROL TOTAL CHLORINE RESIDUAL TOTAL ORGANIC CARBON TOC

TOD TOTAL OXYGEN DEMAND TURB TURRIDITY LIP-DOWN UD

OP.

BUILDING OR

(8)-9

(3)

FACILITY BOUNDARY

PARALLELING LINES

(PARENTHETICAL NUMBER INDICATES

CONNECTING LINES

NON-CONNECTING

THE NUMBER OF

REPRESENTED

SIGNALS

LINES

VOLATILE HYDROCARBONS VHC VIBRATION

VIB DIFFERENCE MULTIPLY DIVIDE ° f(x) CHARACTERIZED RAISE TO THE Nth POWER √ AVG SQUARE ROOT AVERAGE 1:1 REPEAT OR BOOST SELECT HIGHEST SIGNAL

SELECT LOWEST SIGNAL

GAIN OR ATTENUATE

GENERAL NOTES

- 1 COMPONENTS AND PANELS SHOWN WITH A SINGLE ASTERISK
- 2. COMPONENTS SHOWN WITH DOUBLE ASTERISK (**) TO BE FURNISHED UNDER DIVISION 16, ELECTRICAL
- 3. THIS IS A STANDARD LEGEND, THEREFORE, NOT ALL OF THIS INFORMATION MAY BE USED ON THIS PROJECT
- 4. FUTURE IMPROVEMENTS, NOT INCLUDED IN CURRENT



Revision	Date	Ву
Final	4/2/25	ΑE
Re-Scope	5/7/25	ΑE

Re-Scope

1:2 A.Eckhart, P.E. Paul Montgomery, P.E. Katie Klacik, P.E. Checked By Michael Montoya, P.E.



Kathleen Hutchinson

1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

nderson~ Montgomer

Jacobs

999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520


City Of Missoula

Project Title

Garden City Compost Facility Improvements

Sheet Title

PID Symbols and Legend



NOTE:

THIS IS A STANDARD LEGEND SHEET SOME SYMBOLS OR ABBREVIATIONS MAY APPEAR ON THIS SHEET AND NOT ON THE PLANS.



2)	2/12/23		
Revision	Date	Ву	
Final	4/2/25	AE	
Re-Scope	5/7/25	AE	

Re-Scope	5/7/25	AE	
Revision			
	Scope		
Plot Scale			

1:2 A.Eckhart, P.E. Paul Montgomery, P.E. Katie Klacik, P.E. Checked By Michael Montoya, P.E.

Kathleen Hutchinson



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Jacobs

999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520


City Of Missoula

Project Title

Garden City Compost Facility Improvements

Sheet Title

PID Symbols and Legend



NONT AND KATHLEEN KLACIK ONO. 72593 PE W

Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Revision Re-Scope

1:2

A.Eckhart, P.E.

Approved By
Paul Montgomery, P.E.

Approved By
Katie Klacik, P.E.

Checked By
Michael Montoya, P.E.
Designed By
Kathleen Hutchinson

Anderson~ Montgomery

1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Jacobs

999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520

Owner

City Of Missoula


Project Title

Garden City Compost Facility Improvements

Sheet Title

Compost Area No. 1 & Biofilter No. 1

Sheet



CONTANA AND KATHLEEN B KALACIK NO. 72593 PE W

2/	2/12/23			
Revision	Date	Ву		
Final	4/2/25	AE		
Re-Scope	5/7/25	AE		

Re-Scope

Plot Scale 1:2

A.Eckhart, P.E.

Approved By
Paul Montgomery, P.E.

Approved By
Katie Klacik, P.E.

Checked By
Michael Montoya, P.E.
Designed By
Kathleen Hutchinson

Engineer

Anderson~ Montgomery

1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Jacobs

999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520

Owne

City Of Missoula


Project Title

Garden City Compost Facility Improvements

Sheet Title

Compost Area No. 2 & Biofilter No. 2

heet



ON TANGENT ON TANGENT OF THE PROPERTY OF THE P

Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Re-Scope

Plot Scale 1:2

A.Eckhart, P.E.

Approved By
Paul Montgomery, P.E.

Approved By
Katie Klacik, P.E.
Checked By
Michael Montoya, P.E.
Designed By
Kathleen Hutchinson

Kathleen Hutchinson

Anderson~Montgomery

1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Jacobs

999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520

Owner

City Of Missoula


Project Title

Garden City
Compost
Facility
Improvements

Sheet Title

Compost Area Network Diagram

Shee



A A THE THE PARTY OF THE PARTY

Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Revision Re-Scope
Plot Scale
1:2

A.Eckhart, P.E.
Approved By
P.Montgomery, P.E.
Checked By
A.Eckhart, P.E.
Designed By
P.Montgomery, P.E.

ngineer



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Owner

City Of Missoula

Project Title

Garden City Compost Facility Improvements


Sheet Title

Demolition Site Plan

Sheet

 $N \longrightarrow \bigoplus \longleftarrow$

D-1





Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Re-Scope

1:2 Drawn By A.Eckhart, P.E.

A.Eckhart, P.E.
Approved By
P.Montgomery, P.E.
Checked By
A.Eckhart, P.E.
Designed By
P.Montgomery, P.E.



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

wner

City Of Missoula


Project Title

Garden City Compost Facility Improvements

eet Title

Overall Grading Plan

heet





evision	Date	Ву	l
Final	4/2/25	AE	l
-Scope	5/7/25	AE	l
			l
			l

Re-Scope

City Of Missoula

Garden City Compost Facility Improvements


Grading Plan - North





evision	Date	Ву
Final	4/2/25	AE
-Scope	5/7/25	AE







Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

n Re-Scope

Drawn By
A.Eckhart, P.E. Approved By P.Montgomery, P.E. Checked By
A.Eckhart, P.E.
Designed By
P.Montgomery, P.E.




1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

City Of Missoula

Garden City Compost Facility Improvements

Post Bid Revised Site Plan





Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE
		_

Revision Re-Scope

Drawn By
A.Eckhart, P.E.

Approved By
P.Montgomery, P.E.
Checked By
A.Eckhart, P.E.
Designed By
P.Montgomery, P.E.

Engineer



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

humar

City Of Missoula

Project T


Garden City Compost Facility Improvements

Sheet Title

Compost Bays and Biofilters Site Plan

Sheet







Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Re-Scope

Drawn By
A.Eckhart, P.E.

P.Montgomery, P.E.
Checked By
A.Eckhart, P.E.
Designed By
P.Montgomery, P.E.




1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

City Of Missoula

Garden City Compost Facility Improvements

Pre-Compost Containment Bin and Biosolids Bin Site Plan





	Revision	Date	Ву
	Final	4/2/25	AE
	Re-Scope	5/7/25	AE

Revision Re-Scope

t Scale 1:2

A.Eckhart, P.E.

Approved By
P.Montgomery, P.E.

Checked By
A.Eckhart, P.E.

Designed By
P.Montgomery, P.E.

Engineer



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Owner

City Of Missoula


Project Title

Garden City Compost Facility Improvements


Sheet Title

Irrigation Well Site Plan

Sheet



Revision	Date	By
Final	4/2/25	AE
Re-Scope	5/7/25	AE





Revision	Date	By
Final	4/2/25	AE
Re-Scope	5/7/25	AE
		_

Revision Re-Scope

1:2 rawn By A.Eckhart, P.E.

P.Montgomery, P.E.

Checked By

A.Eckhart, P.E.

Designed By
P.Montgomery, P.E.

Engineer



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Owner

City Of Missoula

Project Title

Garden City Compost Facility Improvements

Sheet Title

Lift Station to Drying Bed Drain Plan & Profile

heet



Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

NOTES:

THE CONTRACTOR SHALL SECURE AUTHORIZATION TO DISCHARGE UNDER MDEQ'S GENERAL PERMIT FOR STORM WATER DISCHARGES ASSOCIATED WITH CONSTRUCTION ACTIVITY MTR100000 AND PREPARE AN APPROVABLE STORM WATER POLLUTION PREVENTION PLAN (SWPPP). THE SWPPP SHALL IDENTIFY BEST MANAGEMENT PRACTICES (BMPs) TO ADDRESS POTENTIAL RUNOFF, EROSION AND SEDIMENT CONTROL ISSUES AT THE PROJECT SITE. SUGGESTED LOCATIONS AND TYPES OF BMP'S ARE SHOWN IN THE DRAWING, YET ARE NOT MEANT TO BE ALL-INCLUSIVE. CONTRACTOR SHALL BE SOLEYLY RESPONSIBLE FOR SELECTING THE MOST APPROPRIATE BMP, INSTALLATION, PROPER MAINTENANCE AND REMOVAL OF THE BMP UPON PROJECT COMPLETION.

EC - EROSION CONTROL BMP

——EC

SC - SEDIMENT CONTROL BMP

----s

RoR - RUN ON/OFF BMP

RoR -

OTr - OFFSITE TRACKING

——OTr











Revision	Date	By
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Re-Scope Plot Scale

A.Eckhart, P.E.

Approved By
P.Montgomery, P.E.

Checked By
A.Eckhart, P.E.

Designed By
P.Montgomery, P.E.

Engineer



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

wner

City Of Missoula

Project Title

Garden City Compost Facility Improvements

Sheet Title

Runoff Control Plan

Sheet

NOTES:


- 1. KEEP CONCRETE CLEAR OF JOINT AND JOINT ACCESSORIES
- 2. POUR THRUST BLOCKING AGAINST 3/4" MINUS GRAVEL OR STRUCTURAL FILL. 3/4" MINUS GRAVEL OR STRUCTURAL FILL SHALL BE AGAINST UNDISTURBED EARTH.
- REQUIRED VOLUMES AND BEARING AREAS SHALL BE AS SHOWN IN THE TABLE AND ADJUSTED, IF NECESSARY, TO CONFORM TO THE TEST PRESSURE(S) AND ALLOWABLE SOIL BEARING STRESS OF 2,000 LBS/SQFT.
- THRUST BLOCK VOLUMES FOR VERTICAL BENDS HAVING UPWARD RESULTANT THRUSTS ARE BASED ON TEST PRESSURE OF 150 PSIG AND THE WEIGHT OF CONCRETE = 4,050 LBS PER CUBIC YARD. TO COMPUTE VOLUMES FOR DIFFERENT TEST PRESSURES USE THE FOLLOWING **EQUATION:**
 - ACTUAL VOLUME = (TEST PRESSURE/150) X (TABLE VOLUME).
- 5. BEARING AREAS FOR HORIZONTAL BEND THRUST BLOCKS ARE BASED ON TEST PRESSURE OF 150 PSIG AND AN ALLOWABLE SOIL BEARING STRESS OF 2,000 LBS/SQFT. TO COMPUTE BEARING AREAS FOR DIFFERENT TEST PRESSURES US THE FOLLOWING EQUATION:
 - $B_1 = B(13.33)(P_1/2000)$ WHERE:
 - P1 = ACTUAL TEST PRESSURE, PSIG
 - B = COMPUTED BEARING AREA
 - B = BEARING AREA FROM TABLE
- VERTICAL BENDS HAVING DOWNWARD RESULTANT THRUSTS AND HORIZONTAL BENDS, HAVE THE SAME THRUST BLOCK REQUIREMENTS.
- BEARING AREAS, VOLUMES, AND SPECIAL BLOCKING DETAILS SHOWN ELSEWHERE IN THESE PLANS TAKE PRECEDENCE OVER THIS
- THRUST BLOCK BEARING AREA SHALL NOT BE LESS THAN 1.0 SQFT.
- TEST PRESSURES ARE INDICATED IN THE SPECIFICATIONS AND THE ALLOWABLE SOIL BEARING STRESS IS 2,000 LBS/SQFT.
- 10. THE USE OF RESTRAINED JOINT SYSTEMS WILL BE ACCEPTED AS AN ALTERNATIVE TO CONVENTIONAL CONCRETE THRUST BLOCKING.
- 11. CONTRACTOR SHALL PROVIDE THRUST BLOCKING FOR ALL BURIED FITTINGS AND VALVES.

VOLUME OF THRUST BLOCK IN CUBIC YARDS (VERTICAL BENDS)					
FITTING SIZE	BEND ANGLE				
(INCHES)	45°	22-1/2°	11-1/4°		
4	0.8	0.3	0.1		
6	2.0	0.8	0.3		
8	3.0	1.1	0.4		
10	4.5	1.7	0.7		
12	5.4	2.4	1.0		
14	8.6	3.2	1.3		
16	11.1 4.2 1.7				
18	14.1	5.3	2.2		
20	17.3	6.6	2.7		
24	24.2	9.2	3.8		

VERTICAL BEND REBAR					
FITTING SIZE	ROD SIZE	EMBEDMENT			
12" AND LESS	#6	30"			
14" - 16"	#8	36"			
18" - 20"	#10	36"			
24"	#11	42"			

NOTE:

EPOXY COATED REBAR OVER FITTING AND EMBEDDED IN CONCRETE (SEE TABLE FOR SIZES)




	BEARING ARE	EA OF THRUS	T BLOCKS I	N SQFT. (H	ORIZONTAL	BENDS)	
FITTING SIZE	TEE, WYE, PLUG, OR	90° BEND, PLUGGED	TEE, PLUGGED RUN		Е	BEND ANGL	E
(INCHES)	CAP	CROSS	A ₁	A ₂	45°	22-1/2°	11-1/4°
4	1.3	1.8	1.3	1.8	1.0	1.0	
6	3.0	4.2	3.0	4.2	2.3	1.2	1.0
8	5.3	7.6	5.3	7.6	4.1	2.1	1.0
10	8.3	11.8	8.3	11.8	6.4	3.3	1.6
12	12.0	17.0	12.0	17.0	9.2	4.7	2.4
14	16.3	23.1	16.3	23.1	12.5	6.4	3.2
16	21.4	30.2	21.4	30.2	16.3	8.3	4.2
18	27.0	32.0	27.0	32.0	20.7	10.5	5.3
20	33.4	47.2	33.4	47.2	25.5	13.0	6.5
24	40.3	55.0	40.3	55.0	35.7	18.0	9.0


- * EACH AREA (A/2) IS HAVE OF TABULATED TOTAL AREA
- ** RESTRAINED PLUG

VALVE THRUST BLOCK DIMENSIONS							
VALVE	REBAR		100 PSI			150 PSI	
SIZE	SIZE	Α	В	С	Α	В	С
4"	#6	2.0'	2.0'	2.0'	2.0'	2.0'	2.0'
6"	#6	2.0'	2.0'	2.0'	2.0'	2.0'	2.0'
8"	#6	2.0'	2.0'	2.0'	2.0'	2.0'	2.0'
10"	#6	2.0'	2.0'	2.0'	2.5'	2.5'	2.0'
12"	#6	2.3'	2.0'	2.0'	3.0'	3.0'	2.7'
14"	#8	2.3'	2.0'	2.3'	3.4'	3.0'	3.0'
16"	#9	3.0'	3.0'	2.9'	4.3'	3.0'	3.0'
18"	#10	3.7'	3.0'	3.0'	5.4'	3.0'	3.0'
20"	#10	3.9'	3.3'	3.3'	5.7'	3.3'	3.3'
24"	#11	4.3'	4.0'	4.0'	6.4'	4.0'	4.0'

DIMENSION 'A' IS WIDTH OF THRUST **BLOCK (PERPENDICULAR TO PAGE)**




NO SCALE



- NO PAYMENT SHALL BE MADE FOR ADJUSTMENT OF VALVE BOXES TO FINAL GRADE.
- COMPACT ALL BACKFILL AROUND THE VALVE BOX UPPER SECTION BY MEANS OF HAND TAMPING.
- CONTRACTOR SHALL PROVIDE OWNER WITH 1 VALVE WRENCH.
- ALL CONCRETE AND CONCRETE THRUST BLOCKING SHALL BE ENCASED IN 3/4" MINUS GRAVEL OR STRUCTURAL FILL.







VALVE BOX TO BE ADJUSTED TO FINISHED

Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Re-Scope 1:2

A.Eckhart, P.E. P.Montgomery, P.E. A.Eckhart, P.E.

P.Montgomery, P.E.



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

City Of Missoula

Garden City Compost Facility **Improvements**

Civil Details

DURING CROSSINGS, STRUCTURAL SUPPORT OF THE SEWER OR STORM DRAIN SHALL BE PROVIDED BY THE CONTRACTOR. THE CONTRACTOR SHALL BE RESPONSIBLE FOR PREVENTING DAMAGE TO ANY EXISTING PIPES. IF AN EXISTING PIPE IS DAMAGED DUE TO CONTRACTOR NEGLIGENCE, THE PIPE SHALL BE REPAIRED AT NO ADDITIONAL COST TO THE OWNER.

Vertical Pipe Adjustment

- 1. WHERE TRENCH PASSES THROUGH UNIMPROVED SURFACES: THE TOPSOIL SHALL BE REMOVED AND REPLACED A MINIMUM OF 12" FROM THE EDGE OF THE TRENCH OPENING.
- 2. WHERE TRENCH PASSES THROUGH EXISTING GRAVEL: THE GRAVEL SHALL BE REMOVED AND REPLACED A MINIMUM OF 12" FROM THE EDGE OF THE TRENCH OPENING.
- WHERE TRENCH PASSES THROUGH EXISTING PAVEMENT: THE PAVEMENT SHALL BE CUT ALONG A NEAT VERTICAL LINE A MINIMUM OF 12" FROM THE EDGE OF THE TRENCH OPENING, JUST PRIOR TO PAVING.
- WHERE TRENCH PASSES THROUGH EXISTING PAVEMENT: SAWCUT THE ASPHALT ALONG A NEAT VERTICAL LINE PER LIMITS SHOWN ON THE PLANS, JUST PRIOR TO PAVING, WHERE IMPORTED TRENCH BACKFILL IS NOT USED. SEPARATION/STABILIZATION FABRIC, PROPEX GEOTEX 801 NON-WOVEN GEOTEXTILE FABRIC OR APPROVED EQUAL WILL BE USED.
- VERIFY THAT COMPACTION METHODS ARE COMPARABLE WITH PIPE MANUFACTURER'S RECOMMENDATIONS. ANY DAMAGE TO THE PIPE WILL BE THE CONTRACTOR'S RESPONSIBILITY.

- TRENCH SHALL BE CONSTRUCTED TO OSHA SPECIFICATIONS FOR EXCAVATION. DRAWINGS DO NOT SHOW TRENCH DIMENSIONS OR BACK-SLOPES THAT MAY BE REQUIRED. CONTRACTOR REQUIRED TO DETERMINE WHICH OSHA SPECIFICATIONS ARE APPLICABLE
- ALL SPOILS SHALL BE REMOVED AND DISPOSED OF AT AN APPROVED LOCATION.
- INSTALL 4" OF RIGID INSULATION THE FULL WIDTH OF THE TRENCH IN AREAS SHOWN ON PLANS.
- ALL ROCKS GREATER THAN 12" IN ANY DIMENSION SHALL BE HAULED OFF SITE AND DISPOSED OF PROPERLY.
- 10. NO ROCKS OR LUMPS LARGER THAN 2" IN ANY DIMENSION SHALL BE ALLOWED WITHIN 6" OF THE PIPE.
- 11. USE SUITABLE NATIVE MATERIAL FOR BACKFILL. SEE TECHNICAL SPECIFICATIONS FOR CONDITIONS REQUIRING IMPORTED TRENCH BACKFILL

WITH CONCRETE. SURFACE PREPARATION: - BLAST NEAR-WHITE PRIME COAT: 4' 6" - CARBOLINE CARBOCOAT 150-3.0 MIL DFT TWO FINISH COATS: - CARBOLINE CARBOCOAT 30 OSHA YELLOW - 3.0 MIL DFT TOTAL FINISHED GRADE 3' 6' -18" Ø CONCRETE -COMPACT NATIVE MATERIAL (TYP.)

NOTE:


4" Ø STEEL PIPE FILLED-

BUILDING FACE, CONCRETE PADS, OR OTHER DRIVING HAZARDS SHALL BE A MINIMUM OF 12" FROM THE CENTERLINE OF PIPE BOLLARD.

Typical Pipe Bollard Detail 2

NOTES CONTINUED:

- 12. USE LABELED AND COLOR-CODED TAPE FOR THE APPROPRIATE UTILITY PIPE, PLACED 18" MAXIMUM BELOW FINISHED SURFACE.
- 13. SEED, FERTILIZE, AND MULCH ALL DISTURBED AREAS WHICH ARE NOT PAVED, CONCRETED, SODDED, OR GRAVELED PER SPECIFICATIONS
- 14. FOR WATER MAINS AND FORCE MAINS TRACER WIRE SHALL BE TAPED TO TOP OF ALL PLASTIC PIPE (PVC, POLYTHYLENE, AND HDPE) AND BROUGHT UP FIRE HYDRANTS AND VALVE PIPE CASINGS.
- COMPACTION REFERS TO PERCENT OF MAXIMUM DENSITY DETERMINED BY A STANDARD PROCTOR. ASTM D698-91. TRENCHES EXCEEDING 10 FEET IN DEPTH SHALL BE COMPACTED TO 98% OF MAXIMUM DENSITY PER ASTM D698-91.
- 16. FINISHED GRADE MUST MATCH THE ORIGINAL EXISTING GRADE WHERE PIPE IS INSTALLED UNLESS OTHERWISE NOTED.
- 17. REFER TO GENERAL NOTES FOR ADDITIONAL REQUIREMENTS.



Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Re-Scope 1:2

A.Eckhart, P.E. P.Montgomery, P.E. A.Eckhart, P.E

P.Montgomery, P.E.


1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

City Of Missoula

Garden City Compost Facility Improvements

Civil Details

CD-2




Pipe Bedding & Backfill Details 3

NOTES:


- COAT FLOOR SLEEVE WITH SPECIFIED PAINT SYSTEM BEFORE CONCRETE PLACEMENT.
- PROVIDE WATERPROOF FIRESTOPPING FOR FIRE RATED FLOOR CONDITION.

Typical Floor Sleeve Detail 1
NO SCALE ~



NOTE: INSTALL WALL PIPE FOR FLOOR
PENETRATIONS AS PER MANUFACTURERS
RECOMMENDATIONS REGARDING LAY LENGTH AND
AND FL/MJ CLEARANCE FROM TOP/BOTTOM OF SLAB.

Typical Floor Penetration Detail 2 NO SCALE ~



Typical Yard Hydrant Assembly Detail 3 NO SCALE C-9



Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Revision Re-Scope

Drawn By
A.Eckhart, P.E.
Approved By
P.Montgomery, P.E.
Cheeked By
A.Eckhart, P.E.

Designed By
P.Montgomery, P.E.



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Owner

City Of Missoula

Project Title


Garden City Compost Facility Improvements

heet Title

Civil Details

Sheet

CD-3




NOTE:
DEPENDING ON PIPING THE CLEANOUT IS CONNECTING TO THERE
SHALL EITHER BE TWO 45° BENDS OR ONE 45° BEND AND ONE WYE.

Exterior Cleanouts 4 NO SCALE ~

- PROVIDE NEOPRENE WAFFLE ISOLATION PAD. SIMILAR TO MASON TYPE "W" OR KORFUND KORPAD40. UNDER SUPPORT FOOT WHEN PIPING IS ISOLATED OR SUPPORT IS ADJACENT TO MECHANICAL EQUIPMENT.
- FOR BASE HEIGHT AND FLANGE DIMENSIONS, SEE TABLE BELOW.


	DIMENSION TABLE					
PIPE					ı	Ξ.
SIZE	A	В	С	D	MIN	MAX
2-1/2"	2-1/2"	3-1/2"	9"	1-1/2"	8"	13"
3"	2-1/2"	3-3/4"	9"	1-1/2"	8-1/4"	13-1/4"
3-1/2"	2-1/2"	4"	9"	1-1/2"	8-1/2"	13-1/2"
4"	3"	4-1/4"	9"	2-1/2"	9-1/4"	14"
5"	3"	4-7/8"	9"	2-1/2"	10"	14-3/4"
6"	3"	5-1/2"	9"	2-1/2"	10-1/2"	15-1/4"
8"	3"	6-7/8"	9"	2-1/2"	11-3/4"	16-1/2"
10"	3"	8-1/2"	9"	2-1/2"	13-1/2"	18-1/4"
12"	3"	9-15/16"	9"	2-1/2"	15"	19-3/4"
14"	4"	10-15/16"	11"	3"	16-1/4"	20-3/4"
16"	4"	12-3/8"	11"	3"	17-3/4"	22-1/4"

Pipe Support Detail 1 NO SCALE




- TOTAL LOADING ON EACH CONCRETE INSERT OR OTHER TYPE HANGER ROD ANCHOR SHALL NOT EXCEED MANUFACTURER'S RECOMMENDED LOADING.
- FOR STEEL PIPE USE GRINNELL FIGURE 260.

Typical Pipe Hanger 3




PROVIDE S.S. COMPONENTS FOR SUBMERGED APPLICATIONS OR WHEN SUPPORT IS INSIDE A BURIED STRUCTURE.

Heavy Duty Pipe Support 2 NO SCALE



CLAMP, BOLTS AND NUTS TO BE STAINLESS STEEL AND SIZED AS REQUIRED.

Vertical Pipe Support 4



Biofilter Header Pipe Support 5

ALL BIOFILTER PIPE SUPPORTS SHALL HAVE A 2'x2'x6" THICK SLAB POURED WITH REBAR 1' O.C.E.W. CENTERED IN THE **SLAB WITH 3" CLEAR ON ALL SIDES.**



Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Re-Scope 1:2

A.Eckhart, P.E. P.Montgomery, P.E. A.Eckhart, P.E. P.Montgomery, P.E.



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

City Of Missoula

Project Title

Garden City Compost Facility Improvements


Pipe **Supports**

CD-4


• FOR INSULATED PIPES, USE GRINNELL FIGURE 167 (INSULATION PROTECTION SHIELD).

- 6. CONCRETE SHELVES SHALL SLOPE TOWARD THE CHANNEL(S) AT 1" PER FOOT.
- 7. PROVIDE FILL MATERIAL, SLOPED AT 2 HORIZONTAL TO 1 VERTICAL FOR COVERS SET ABOVE EXISTING GROUND LEVEL.
- 8. CONSTRUCT SHELVES PER LATEST EDITION OF MPW.
- 9. PROVIDE 3" GROUT SPACE AROUND ALL PIPE. ALL JOINTS SHALL BE GROUTED WATERTIGHT. CONFORM TO MANHOLE LINER MANUFACTURER'S RECOMMENDATIONS.
- 10. NEW MANHOLES SHALL BE COATED WITH AN EXTERIOR DAMPPROOFING; BITUMINOUS COAT OR COAL TAR EPOXY.
- 11. FINISHED MANHOLES SHALL BE IN ACCORDANCE WITH LATEST EDITION OF MPWSS STANDARD SPECIFICATIONS.
- 12. STEPS SHALL BE PLACED AT 90° TO THE LINE OF SEWER PIPE WHERE APPLICABLE. STEPS ARE ROTATED IN DRAWING FOR CLARITY.
- 13. PROVIDE ALL SHORING NECESSARY TO PROTECT EXISTING STRUCTURES AND INFRASTRUCTURE.
- 14. MANHOLES SHALL EITHER UTILIZE A BARREL SECTION & A FLAT LID OR A CONICAL SECTION, SEE DRAWINGS FOR SPECIFIC MANHOLE DETAILS.

Standard Sanitary Sewer Manhole 1



CONFIGURATION MAY VARY



CHANNEL SECTION

NOTES:

- SLOPE ALL SHELVES TO CHANNEL AT 1" PER FOOT.
- ALL NEW HOLES SHALL BE CORED AND LARGE ENOUGH FOR WATERTIGHT SEAL. GROUT SEAL IN PLACE WITH NON-SHRINK GROUT.
- ROTATE CONE AND STAIRS SUCH THAT STAIRS ARE NOT ABOVE CHANNELS.
- RECONSTRUCT FLOW CHANNEL IN ACCORDANCE WITH MPWSS STANDARD DRAWING NO. 02720-7.
- MANHOLE CONFIGURATIONS MAY VARY FROM DETAIL DEPICTED ABOVE.

Modify Existing Manhole 2
NO SCALE ~



Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Revision Re-Scope

A.Eckhart, P.E.
Approved By
P.Montgomery, P.E.
Checked By
A.Eckhart, P.E.

1:2

P.Montgomery, P.E.

Ingineer



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Own

City Of Missoula


Project Title

Garden City Compost Facility Improvements

Sheet Title

Manhole Details

S





Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Revision Re-Scope
Plot Scale

A.Eckhart, P.E.

Approved By
P.Montgomery, P.E.

Checked By
A.Eckhart, P.E.

A.Ecknart, r.E.

Designed By
P.Montgomery, P.E.

nginoor



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Owner

City Of Missoula


Project Title


Garden City Compost Facility Improvements

Sheet Title

Catch Basin 1 Details

Shee





 CONCRETE HATCHING NOT SHOWN FOR DRAWING CLARITY.

Catch Basin 2 Section

NOTE:
• PIPES AND CONCRETE SLAB/APRON ROTATED FOR DRAWING CLARITY.



Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Re-Scope 1:2

A.Eckhart, P.E. Approved By
P.Montgomery, P.E.

Checked By
A.Eckhart, P.E.
Designed By
P.Montgomery, P.E.



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

City Of Missoula

Project Title

Garden City Compost Facility Improvements

Sheet Title

Catch Basin 2 **Details**

- ① 6' DIAMETER CONCRETE STRUCTURE 8" THICK MONOLITHIC BOTTOM
- ② FIBERGLASS REINFORCED PLASTIC ENCLOSURE BY GORMAN RUPP
- ③ VAUGHN CHOPPER PUMP WITH SLIDE RAIL MODEL SK41 (TYP. OF 2)
- 4 8" SDR 35 PVC FROM CATCH BASIN 3 INV. ELEV. 3149.95
- ⑤ PSX MANHOLE BOOT
- 6 4" DI PIPE DISCHARGE INV. ELEV. 3152.20
- 7 LINKSEAL
- ® 2" SCH. 40 STEEL PIPE GUIDE RAIL WITH SUPPORT BRACKETS (TYP. OF 4)
- 9 UPPER GUIDE RAIL BRACKET
- (0) COMPACTED NATIVE MATERIAL
- 11-24" OF STRUCTURAL FILL
- 12 PROPEX GEOTEXT 801 NON-WOVEN GEO-TEXTILE
- 13 8"x8" FILLET NON-SHRINK GROUT
- (14) 4" FLANGED CHECK VALVE (TYP. OF 2)
- 15 4" FLANGED PLUG VALVE (TYP. OF 2)
- (6-4" DI FL 90° BEND (TYP. OF 3)
- (7) 4" DI FL TEE
- (8)-LIFT STATION VENT
- 19 SUBMERSIBLE PUMP OIL RESERVOIR
- 20 SUBMERSIBLE PUMP OIL HOSE (TYP. OF 2) 21 LIFT STATION CONTROL PANEL

- 22-4" SDR 35 FROM CONDENSATE SUMP INV. IN ELEV. 3146.00

- ALL FORCEMAIN PIPING SHALL BE 4" DUCTILE IRON
- ATTACH PUMP LIFTING CHAIN TO STRUCTURE AS PER
- MANUFACTURER'S RECOMMENDATIONS.
- MOUNT OIL RESERVOIR IN ABOVE GROUND STRUCTURE. ROUTE OIL HOSE PER MANUFACTURER'S
- RECOMMENDATIONS.
- PUMP SHALL UTILIZE A BASE BEND THAT IS COMPATIBLE
- WITH THE PIPING GALLERY ENCLOSURE.

PUMP ELEVATIONS:


3149.50 - HIGH LEVEL ALARM


3148.00 - LAG PUMP ON


3147.00 - LEAD PUMP ON

3145.00 - LAG PUMP OFF

3144.00 - LEAD PUMP OFF 3143.00 - LOW LEVEL ALARM
















Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

evision			
Re-Scope			

1:2
Drawn By
A.Eckhart, P.E.
Approved By
P.Montgomery, P.E.
Checked By
A.Eckhart, P.E.
Designed By

P.Montgomery, P.E.





1064 N. Warren Helena, MT 59601 Phone (406) 449-3303


City Of Missoula

Project Title

Garden City Compost Facility Improvements

Sheet Title

Lift Station Plan



Der Andrews

Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Re-Scope
Plot Scale
1:2
Drawn By
A.Eckhart, P.E.

Approved By
P.Montgomery, P.E.
Checked By
A.Eckhart, P.E.

Designed By
P.Montgomery, P.E.

Engineer



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Owner

City Of Missoula


Project Title

Garden City Compost Facility Improvements

Sheet Title

Lift Station Section

She



Constant of the second of the

	_	- n
Revision	Date	By
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Revision Re-Scope

1:2 Drawn By

A.Eckhart, P.E.

Approved By
P.Montgomery, P.E.

Checked By
A.Eckhart, P.E.

Designed By
P.Montgomery, P.E.

Engineer



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Owner

City Of Missoula

Project Title

Garden City Compost Facility Improvements

Sheet Title


Irrigation
Well Details

Sheet

CD-12

GENERAL WELL NOTES:

- CONSTRUCT WELL IN ACCORDANCE WITH THE WELL DRILLER'S REGULATIONS, ARM 36 CHAPTER 21
- ALL DIMENSIONS AND PIPE LENGTHS ARE TO BE ESTABLISHED IN THE FIELD AFTER WELL IS DRILLED AND LITHOLOGY IS KNOWN.
- PUMP POWER CABLE SHALL BE THWN OR THHN INSULATED AND ATTACHED TO PUMP DROP PIPE AT NO GREATER THAN 10-FOOT INTERVALS.





Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

1:2 A.Eckhart, P.E.

P.Montgomery, P.E. Checked By
A.Eckhart, P.E. Designed By
P.Montgomery, P.E.



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

City Of Missoula


Project Title

Garden City Compost Facility Improvements

Sheet Title

Irrigation Plumbing Diagram

CD-13





Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Re-Scope 1:2

A.Eckhart, P.E. P.Montgomery, P.E. Checked By
A.Eckhart, P.E.

Designed By
P.Montgomery, P.E.



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

City Of Missoula


Project Title

Garden City Compost Facility Improvements

Sheet Title

Control Building Plan

CB-1



evision	Date	Ву
Final	4/2/25	AE
-Scope	5/7/25	AE


A.Eckhart, P.E. P.Montgomery, P.E.



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Garden City Compost Facility Improvements

> Building North & South





Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

1:2

A.Eckhart, P.E. P.Montgomery, P.E. Checked By
A.Eckhart, P.E.
Designed By
P.Montgomery, P.E.



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303


City Of Missoula


Project Title

Garden City Compost Facility Improvements


Control Building East & West **Elevations**

CB-3





Control Building Corner Footing Anchors NO SCALE



Revision	Date	By
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Re-Scope

1:2

Drawn By
A.Eckhart, P.E. A.E.Chiari, F.E.
Approved By
P.Montgomery, P.E.
Checked By
A.Eckhart, P.E.
Designed By
P.Montgomery, P.E.



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303


City Of Missoula

Garden City Compost Facility Improvements

Sheet Title

Control Building Anchors

CB-4



Final 4/2/25 AE Re-Scope 5/7/25 AE

Re-Scope

A.Eckhart, P.E. P.Montgomery, P.E.

T.Williams, P.E.

T.Pipher, P.E.

1064 N. Warren Helena, MT 59601 Phone (406) 449-3303


Jacobs

999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520

City Of Missoula

Garden City Compost Facility Improvements

Compost **Bays Piping**





Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

A.Eckhart, P.E.

P.Montgomery, P.E. necked By A.Eckhart, P.E.

T.Williams, P.E.

P.Montgomery, P.E.

Designed By T.Pipher, P.E.



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Jacobs

999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520

City Of Missoula


Garden City Compost Facility Improvements


Compost **Bay Piping Details**

- ①- COMP-FAN-X: 5 HP BLOWER (CINCINNATI PB-15A4 CW BH OR PRE-APPROVED EQUAL)
- ② 8"x12" S.S. 16 GAUGE DUCT
- ③ 12"x12"x8" S.S. 16 GAUGE DUCT TEE
- 4 FLxS.S. ADAPTER (TYP. ALL TRANSITIONS FROM S.S. TO FLANGE FITTINGS)
- ⑤ 12" FLxFL DAMPER (GREENHECK HCDR-250 OR EQUAL)
- 6 8" FLXFL DAMPER (GREENHECK HCDR-250 OR EQUAL)
- 7 12" S.S. 16 GAUGE DUCT FIELD FIT
- ® 8" S.S. 16 GAUGE DUCT FIELD FIT
- 9 12" S.S. 16 GAUGE DUCT 90° BEND
- (1) 8" S.S. 16 GAUGE DUCT SHORT RADIUS 90° BEND
- 11 30" HDPE SDR 26
- (12) 12" S.S. 16 GAUGE DUCT TEE
- (3) 12" S.S. TO 16" HDPE SDR 26 ADAPTER
- (14) 12" HDPE SDR 26 FIELD FIT
- 15 12" HDPE SDR 26 BUTT FUSE TEE
- (6-12"x12"x6" HDPE SDR 26 BUTT FUSE TEE
- 17 12" HDPE SDR 26 BUTT FUSE CAP
- (8) 6" HDPE SDR 26 BUTT FUSE WYE
- (19) 6" HDPE SDR 26 45° BEND
- 20-6" HDPE SDR 26 PIPE FIELD FIT
- 21-6" WING NUT PIPE PLUG (TYP.)
- 22- CLEANOUT FRAME (TYP.) 23- FOUL AIR TEST PORT SEE DETAIL 4
- 24-12"x4" HDPE SDR 26 BUTT FUSE REDUCER
- 25- 4" HDPE SDR 26 BUTT FUSE TEE (TYP.) 26-4" HDPE SDR 26 BUTT FUSE 45° BEND (TYP.)
- (27)- 4" HDPE SDR 26 CONDENSATE PIPING
- 28-12" ENDUSTRA INTAKE FILTER WITH S.S. MEDIA OR APPROVED EQUAL
- 29-12" S.S. 16 GAUGE DUCT SHORT RADIUS 90° BEND 30-4" WING NUT PIPE PLUG
- (31)- HOLZ FLEXIBLE JOINT STYLE 942 OR EQUAL
- 32- PIPE BOLLARD SEE DETAIL 2

NOTE:

- CONDENSATE PIPING ELEVATION VARIES SEE COMPOST CONDENSATE DRAWINGS FOR DETAILS. SHEETS M-15 THROUGH M-16.
- ALL FLANGE ADAPTERS SHALL UTILIZE AN IRON FLANGE.
- ALL PIPES PASSING THROUGH A CONCRETE SLAB SHALL UTILIZE A SLEEVE, SEE CIVIL DETAILS.









Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Re-Scope

1:2

A.Eckhart, P.E.

P.Montgomery, P.E. Checked By
A.Eckhart, P.E.

T.Williams, P.E.

P.Montgomery, P.E.
Designed By T.Pipher, P.E.



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Jacobs


999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520

City Of Missoula

Project Title

Garden City Compost Facility Improvements

Compost Bay Aeration Piping **Details**



Distriction of the second of t

 Revision
 Date
 By

 Final
 4/2/25
 AE

 Re-Scope
 5/7/25
 AE

Re-Scope
Plot Scale

A.Eckhart, P.E.
Approved By
P.Montgomery, P.E.
Checked By

A.Eckhart, P.E.
necked By
T.Williams, P.E.
esigned By

P.Montgomery, P.E.
Designed By
T.Pipher, P.E.

Anderson~ Montgomery

1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Jacobs

999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520

Owner


City Of Missoula

Project Title

Garden City Compost Facility Improvements

neet Title

Compost
Bay
Aeration
Piping
Sections





	T _	-
Revision	Date	By
Final	4/2/25	AE
Re-Scope	5/7/25	AE

A.Eckhart, P.E. P.Montgomery, P.E.

Checked By
A.Eckhart, P.E.
Checked By
T.Williams, P.E.

T.Williams, P.E.
Designed By
P.Montgomery, P.E.
Designed By
T.Pipher, P.E.



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Jacobs

999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520


City Of Missoula

Project Title

Garden City Compost Facility |Improvements|

Sheet Title

Biofilter **Bays Piping**



A A STATE OF THE PARTY OF THE P

Revision	Date	By
Final	4/2/25	AE
		AE
Re-Scope	5/7/25	AE

Revision Re-Scope

A.Eckhart, P.E.

Approved By
P.Montgomery, P.E.

hecked By
A.Eckhart, P.E.
hecked By

T.Williams, P.E.

Designed By
P.Montgomery, P.E.

Designed By

T.Pipher, P.E.



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Jacobs

999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520

Owner

City Of Missoula


Project Title

Garden City Compost Facility Improvements

Sheet Title

Biofilter 1 Piping Details

Sheet



Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Re-Scope 1:2

A.Eckhart, P.E. P.Montgomery, P.E.

T Williams P F

P.Montgomery, P.E.
Designed By T.Pipher, P.E.



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Jacobs

999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520

City Of Missoula

Garden City Compost Facility Improvements

Biofilter 1 Piping **Details**





Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Revision Re-Scope

Scale 1:2

A.Eckhart, P.E.

Approved By
P.Montgomery, P.E.

Checked By
A.Eckhart, P.E.

Checked By T.Williams, P.E.

Designed By
P.Montgomery, P.E.
Designed By
T.Pipher, P.E.

Engineer

Anderson~ Montgomery
ONSULTING ENGINEERS

1064 N. Warren
Helena, MT 59601
Phone (406) 449-3303

Jacobs

999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520

Owner

City Of Missoula

Project Title


Garden City
Compost
Facility
Improvements

Sheet Title


Biofilter Details

She


M-8



12" HDPE Biofilter Aeration Lateral End Cap Detail 1 NO SCALE M-7,M-10







Change of the state of the stat

 Revision
 Date
 By

 Final
 4/2/25
 AE

 Re-Scope
 5/7/25
 AE

Revision Re-Scope

rawn By
A.Eckhart, P.E.

P.Montgomery, P.E.
Checked By
A.Eckhart, P.E.

T.Williams, P.E.

P.Montgomery, P.E.
Designed By
T.Pipher, P.E.

Anderson~ Montgomery

1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Jacobs

999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520

Owner


City Of Missoula

Project Title

Garden City Compost Facility Improvements

Sheet Title

Biofilter 2 Piping Details



Final 4/2/25 AE Re-Scope 5/7/25 AE

> Re-Scope 1:2

A.Eckhart, P.E. P.Montgomery, P.E.

A.Eckhart, P.E. T.Williams, P.E.

P.Montgomery, P.E.

Designed By T.Pipher, P.E.

inderson~ Montgomer

1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Jacobs


999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520

City Of Missoula

Project Title

Garden City Compost Facility Improvements

Biofilter 2 Piping **Details**



Final 4/2/25 AE Re-Scope 5/7/25 AE

Re-Scope

A.Eckhart, P.E. P.Montgomery, P.E.

1:2

A.Eckhart, P.E. T.Williams, P.E.

Designed By
P.Montgomery, P.E.
Designed By T.Pipher, P.E.

1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Jacobs


999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520

City Of Missoula

Project Title

Garden City Compost Facility Improvements

Compost Condensate Collection



Distriction of the second of t

 Revision
 Date
 By

 Final
 4/2/25
 AE

 Re-Scope
 5/7/25
 AE

Re-Scope

A.Eckhart, P.E.
Approved By
P.Montgomery, P.E.
Checked By
A.Eckhart, P.E.

1:2

T.Williams, P.E.

P.Montgomery, P.E.

Designed By
T.Pipher, P.E.

Anderson~ Montgomery

1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Jacobs

999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520

Owner

City Of Missoula


Project Title

Garden City
Compost
Facility
Improvements

Sheet Title

Compost Condensate Collection Section

Sheet





Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

ot Scale 1:2

A.Eckhart, P.E.

Approved By
P.Montgomery, P.E.

Checked By
A.Eckhart, P.E.

T.Williams, P.E.

P.Montgomery, P.E.
Designed By
T.Pipher, P.E.

Ingineer

1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Jacobs

999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520

Owner

City Of Missoula


Project Title

Garden City Compost Facility Improvements

Sheet Title

Compost Condensate Sump 1 Details

Sheet



Final 4/2/25 AE Re-Scope 5/7/25 AE

Re-Scope

A.Eckhart, P.E. P.Montgomery, P.E. A.Eckhart, P.E.

1:2

T Williams P F

P.Montgomery, P.E.

Designed By T.Pipher, P.E.

1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Jacobs


999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520

City Of Missoula

Project Title

Garden City Compost Facility Improvements

Foul Air to Biofilter Condensate Collection



Final 4/2/25 AE Re-Scope 5/7/25 AE

Re-Scope

A.Eckhart, P.E. P.Montgomery, P.E. A.Eckhart, P.E.

1:2

T.Williams, P.E.

P.Montgomery, P.E.
Designed By T.Pipher, P.E.

Anderson~ Montgomer

1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Jacobs


999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520


City Of Missoula


Project Title

Garden City Compost Facility Improvements

Foul Air to **Biofilter** Condensate Collection Section







NOTE:

- PIPE PENETRATIONS, CASTING, AND MANHOLE STEPS ROTATED FOR DRAWING CLARITY.
- ALL FLANGE ADAPTERS SHALL UTILIZE IRON FLANGES & STAINLESS STEEL BOLTS/NUTS.



Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Revision Re-Scope Plot Scale

1:2

A.Eckhart, P.E.
Approved By
P.Montgomery, P.E.

Checked By
A.Eckhart, P.E.
Checked By
T.Williams, P.E.

Designed By
P.Montgomery, P.E.
Designed By

T.Pipher, P.E.

Anderson~ Montgomery

1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Jacobs

999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520

Owner

City Of Missoula


Project Title


Garden City Compost Facility Improvements

Sheet Title

Condensate Sump 2 Details

Shee









Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

1:2

A.Eckhart, P.E. P.Montgomery, P.E.

Checked By
A.Eckhart, P.E.
Checked By
T.Williams, P.E.

Designed By
P.Montgomery, P.E.
Designed By
T.Pipher, P.E.

Anderson~ Montgomery

1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Jacobs


999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520

City Of Missoula

Project Title

Garden City Compost Facility Improvements

Biofilter 1 Condensate Cleanout **Details**





Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

1:2

A.Eckhart, P.E. P.Montgomery, P.E.

Checked By
A.Eckhart, P.E. Checked By T.Williams, P.E.

Designed By
P.Montgomery, P.E.
Designed By

T.Pipher, P.E.



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Jacobs

999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520


City Of Missoula

Project Title

Garden City Compost Facility Improvements

Sheet Title

Biofilter 2 Condensate Cleanout **Details**





Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

1:2
Drawn By
A.Eckhart, P.E.
Approved By
P.Montgomery, P.E.
Checked By
A.Eckhart, P.E.

hecked By
T.Williams, P.E.

Designed By
P.Montgomery, P.E.
Designed By
T.Pipher, P.E.

Anderson~ Montgomery

1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Jacobs

999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520

ner

City Of Missoula


Project Title

Garden City Compost Facility Improvements

Sheet Title

Biofilter Bays Irrigation

Sheet



 Revision
 Date
 By

 Final
 4/2/25
 AE

 Re-Scope
 5/7/25
 AE

Revision
Re-Scope

A.Eckhart, P.E.
Approved By
P.Montgomery, P.E.
Checked By
A.Eckhart, P.E.

1:2

T.Williams, P.E.
Designed By
P.Montgomery, P.E.
Designed By
T.Pipher, P.E.

Anderson~ Montgomery

1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Jacobs

999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520

Owner

City Of Missoula


Project Title


Garden City Compost Facility Improvements

Sheet Title

Details


neet






Pressure Connection Installation 2
NO SCALE

STEEL & S.S. DUCT 4" & LARGER



DUCT



Thermowell Installation 3 NO SCALE ~ T.Pipher, P.E.

Engineer

Anderson~ Montgomery

Final 4/2/25 AE Re-Scope 5/7/25 AE

Re-Scope

1:2

A.Eckhart, P.E.

P.Montgomery, P.E.
Checked By
A.Eckhart, P.E.

T.Williams, P.E.

Designed By
P.Montgomery, P.E.
Designed By

1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Jacobs

999 Main Street STE. 1200 Boise, ID 83702 Phone (406) 212-4520

Owner

City Of Missoula

Project Title

Garden City Compost Facility Improvements

Sheet Title

Instrument Details

Sheet


M-30

Pressure Instrument Installation - Diaphragm Seal

NOTES:

 COMPONENTS DESIGNATED WITH AN * ARE SUPPLIED BY THE INSTRUMENT MANUFACTURER.

ADD THERMAL INSULATION FOR OUTDOOR INSTRUMENTS




Field Instrument Mounting - Stanchion 4 NO SCALE

NOTES:

 COMPONENTS DESIGNATED WITH AN * ARE SUPPLIED BY THE INSTRUMENT MANUFACTURER.

 PAINT ALUMINUM IN CONTACT WITH CONCRETE ACCORDING TO SPECIFICATIONS FOR PAINTING.



Type "SS-2" Surge Suppressor Wiring Diagram 5
NO SCALE

ACI	EVIATIONS: American Concrete Institute	LB	Pound
ACI	American Concrete Institute American Institute of Steel		
Construction	American institute of Steel	LD	Development length of reinf
AISI	American Iron and Steel Institute	LF	Linear feet
ANSI	American National Standards Institute	LIN	Linear
ASTM	ASTM International	LONGIT	Longitudinal
ASD	Allowable stress design		
AWS	American Welding Society	MAX	Maximum
CRSI	Concrete Reinforcing Steel Institute	MIN	Minimum
ICC	International Code Council	MFR	Manufacturer
PCA	Portland Cement Association	IVII IX	Manufacturei
WRI	Wire Reinforcement Institute		
		NIC	Not in contract
(E)	Existing	NO	Number
(N)	New	NOM	Nominal
f 'c	Specified compressive strength of	NTS	Not to scale
	concrete, psi		
f_{y}	Minimum specified yield strength of	ОС	On center
	reinforcing steel, psi	OD	Outside diameter
psf	Pounds per square foot used for		
	loads on building or reactions as from	OF	Outside face
	soil on footings	ОН	Opposite hand, overhang
psi	Pounds per square inch used for	OPNG	Opening
	stress or strength of concrete and	OPP	Opposite
	reinforcing bars		-11
kip	1000 pounds	DO	D
ksi	Kips per square inch	PC	Precast
_		PCS	Pieces
C	American Standard Channels	PL	Plane bar, plate
HP	Bearing pile shapes	PLCS	Places
HSS	Hollow structural sections	PROJ	Project
L	Angles	P.A.	Preservative treated
M	Miscellaneous shapes		
MC	Miscellaneous channels	PVMT	Pavement
MT	Structural tees from M-shapes		
S	American Standard Beams	QTY	Quantity
ST	Structural tees from S-shapes	D O	•
TS	Structural tubing	RC	Reinforced concrete
W	Wide-flange shapes	RD	Round
WT	Structural tees from W-shapes	REBAR	Deformed reinforcing bar
		REINF	Reinforcement
ADD'L	Additional	REQ	Require
			•
B, BOT	Bottom	REV	Revision
BO, BOF	Bottom of, bottom of footing		
		SC	Shotcrete
CB	Catch basin, corner bar	SCD	See civil drawings
CIP	Cast-in-place	SCHED	Schedule
CJ	Control joint	SE	
CL, CLR	Clear		Slab edge
CONC	Concrete	SECT	Section
CONST	Construction	SF	Square feet, square footage
CONT	Continuous	SIM	Similar
CONTR JT	Contraction joint	SM	Sheet metal
CTR, CTRD	Center, centered	SMD	See mechanical drawings
CY	Cubic yard		•
		SOG	Slab on ground
DIA	Diameter	SPA	Space
DWG	Drawing	SPCG	Spacing
DWL	Dowel	SQ	Square
		STD	Standard
EA	Each		
EE	Each end	STRUCT	Structural, structures
EF	Each face		
EJ, EXP JT	Expansion joint	T	Top
EL, ELEV	Elevation	TC, TOC	Top of concrete
EOR	Engineer on record	TF, TOF	Top of footing
EQ	Equal	•	
E.S.	Each side	TO	Top of
EW	Each way	TOP	Top of precast, top of pier
EXIST	Existing	TOS	Top of slab, top of steel
EXP	Expansion	TOW, TW	Top of wall
EXT	Extend, exterior		•
LXI	Exteria, exterior	TRANSV	Transverse
FDN, FNDN	Foundation	TYP	Typical
FIN	Finish		
		UNO, UON	Unless noted otherwise
FT	Feet, foot	USO, UOS	Unless shown otherwise
	Footing	030, 003	GINESS SHOWIT UNITED WISE
FTG			
FTG	Galvanized	V, VERT, VT	Vertical
FTG GALV	Galvanized	V, VLIXI, VI	
FTG GALV GC	General contractor	VIF	Verify in field
FTG GALV			Verify in field
FTG GALV GC GR	General contractor	VIF	•
FTG GALV GC GR H, HOR,	General contractor Grade		Verify in field Welded wire fabric
FTG GALV GC GR	General contractor	VIF	Welded wire fabric
FTG GALV GC GR H, HOR, HORIZ, HZ	General contractor Grade Horizontal	VIF	•
FTG GALV GC GR H, HOR, HORIZ, HZ	General contractor Grade Horizontal Inside diameter	VIF	Welded wire fabric
FTG GALV GC GR H, HOR, HORIZ, HZ	General contractor Grade Horizontal Inside diameter Inside face	VIF	Welded wire fabric
FTG GALV GC GR H, HOR, HORIZ, HZ	General contractor Grade Horizontal Inside diameter	VIF	Welded wire fabric
FTG GALV GC GR H, HOR, HORIZ, HZ	General contractor Grade Horizontal Inside diameter Inside face	VIF	Welded wire fabric

00.00 - GENERAL:

- 1. WHERE THERE IS A CONFLICT BETWEEN THESE GENERAL STRUCTURAL NOTES AND A SPECIFIC REQUIREMENT IN THE PLANS AND DETAILS, THE SPECIFIC REQUIREMENT SHALL BE APPLICABLE. WHERE, IN ANY SPECIFIC CASE, DIFFERENT PORTIONS OF THESE DRAWINGS SPECIFY DIFFERENT MATERIALS, METHODS OF CONSTRUCTION OR OTHER REQUIREMENTS, THE MOST RESTRICTIVE SHALL GOVERN.
- 2. PROVISIONS OF A PROJECT MANUAL (SPECIFICATIONS) APPLY AND THE MORE RESTRICTIVE SPECIFICATION BETWEEN THESE DRAWINGS AND THE PROJECT MANUAL SHALL APPLY.
- 3. ALL OMISSIONS OR CONFLICTS, INCLUDING DIMENSIONS, BETWEEN THE VARIOUS ELEMENTS OF THE CONSULTANTS' DRAWINGS AND/OR SPECIFICATIONS SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER BEFORE PROCEEDING WITH ANY WORK
- 4. THE STRUCTURAL DRAWINGS SHALL BE USED IN CONJUNCTION WITH THE CIVIL AND MEP DRAWINGS. PRIMARY STRUCTURAL ELEMENTS AND OVERALL STRUCTURAL LAYOUT ARE INDICATED WITH THE STRUCTURAL PLANS AND DETAILS. SOME SECONDARY ELEMENTS, LAYOUTS, ELEVATIONS, SLOPES, DEPRESSIONS, CURBS, MECHANICAL EQUIPMENT AND ELECTRICAL EQUIPMENT, ARE NOT INDICATED WITH THE STRUCTURAL DRAWINGS. DETAILING AND SHOP DRAWING PRODUCTION FOR THE STRUCTURAL ELEMENTS WILL REQUIRE INFORMATION (INCLUDING DIMENSIONS) CONTAINED IN THE CIVIL, STRUCTURAL, AND MEP DRAWINGS.
- 5. DO NOT SCALE THESE DRAWINGS, USE THE DIMENSIONS SHOWN.
- 6. NO STRUCTURAL MODIFICATIONS, ALTERATIONS, OR REPAIRS SHALL BE MADE WITHOUT PRIOR REVIEW BY THE STRUCTURAL ENGINEER.
- 7. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE MEANS, METHODS AND SAFETY OF ERECTION OF THE STRUCTURE, AND SHALL PROVIDE TEMPORARY SHORING AND BRACING AS THE CONTRACTOR'S METHOD REQUIRES TO PROVIDE ADEQUATE VERTICAL AND LATERAL SUPPORT. TEMPORARY SHORING AND BRACING SHALL REMAIN IN PLACE AS THE CHOSEN METHOD REQUIRES UNTIL ALL PERMANENT MEMBERS ARE IN PLACE AND ALL FINAL CONNECTIONS ARE COMPLETED. THE BUILDING SHALL NOT BE CONSIDERED STABLE UNTIL ALL CONNECTIONS ARE COMPLETE.
- 8. THE CONTRACTOR IS SOLELY RESPONSIBLE FOR ALL SAFETY REGULATIONS, PROGRAMS AND PRECAUTIONS RELATED TO ALL WORK ON THIS PROJECT.
- 9. THE CONTRACTOR IS SOLELY RESPONSIBLE FOR THE PROTECTION OF PERSONS AND PROPERTY EITHER ON OR ADJACENT TO THE PROJECT AND SHALL PROTECT IT AGAINST INJURY, DAMAGE, OR LOSS.

01.00 - BASIS OF DESIGN:

- 1. GOVERNING CODES:
 - A. ASCE 7-16 MINIMUM DESIGN LOADS FOR BUILDINGS & OTHER STRUCTURES.
- 2. RISK CATEGORY: I [], II [X], III [], IV []
- DEAD LOADS:
- A. STRUCTURE SELF-WEIGHT
- 4. LIVE LOADS:
- A. CONCRETE SLABS-ON-GRADE:
- a. 16.5 KIP WHEEL LOAD FROM CASE 921G FRONT END LOADER
- 5. EARTHQUAKE DESIGN DATA:
- MAPPED SPECTRAL RESPONSE ACCELERATION, S_S=0.44 AND S₁=0.13
- SITE CLASS: A [], B [], C [], D [X], E [], F []
- DESIGN SPECTRAL RESPONSE ACCELERATION, S_{DS}=0.41 AND S_{D1}=0.23
- 6. GEOTECHNICAL DATA:
- A. SOURCE: GEOTECHNICAL INVESTIGATION AND REPORT WAS PROVIDED FOR. BY PIONEER TECHNICAL SERVICES, REPORT TITLE, "GARDEN CITY COMPOST GEOTECHNICAL REPORT", DATED FEB. 9, 2024.
- B. SOIL BEARING PRESSURE (ASD): 3,000 PSF (STRUCTURAL FILL)
- C. COEFFICIENT OF FRICTION: 0.5
- D. EQUIVALENT FLUID PRESSURE:
 - 1. ACTIVE CASE: 38 PSF/FT
 - 2 AT REST CASE: 60 PSF/FT
 - 3. PASSIVE CASE: 480 PSF/FT
- E. ONE-THIRD STRESS INCREASE FOR WIND OR EARTHQUAKE LOADS

01.14 - SPECIAL INSPECTION:

- 1. SPECIAL INSPECTIONS SHALL BE COMPLETED.
- 2. SPECIAL INSPECTOR QUALIFICATIONS: THE SPECIAL INSPECTOR SHALL PROVIDE WRITTEN DOCUMENTATION TO THE BUILDING OFFICIAL DEMONSTRATING HIS OR HER COMPETENCE AND RELEVANT EXPERIENCE OR TRAINING.
- ACCESS FOR SPECIAL INSPECTION: THE CONSTRUCTION OR WORK FOR WHICH SPECIAL INSPECTION IS REQUIRED SHALL REMAIN ACCESSIBLE AND EXPOSED FOR SPECIAL INSPECTION PURPOSES UNTIL THE REQUIRED SPECIAL INSPECTIONS ARE COMPLETE.
- 4. REPORT REQUIREMENT: SPECIAL INSPECTORS SHALL KEEP RECORDS OF INSPECTIONS. THE SPECIAL INSPECTOR SHALL FURNISH INSPECTION REPORTS TO THE BUILDING OFFICIAL, AND TO THE REGISTERED DESIGN PROFESSIONAL IN RESPONSIBLE CHARGE. REPORTS SHALL INDICATE THAT WORK INSPECTED WAS OR WAS NOT COMPLETED IN CONFORMANCE TO APPROVED CONSTRUCTION DOCUMENTS. DISCREPANCIES SHALL BE BROUGHT TO THE IMMEDIATE ATTENTION OF THE CONTRACTOR FOR CORRECTION. IF THEY ARE NOT CORRECTED, THE DISCREPANCIES SHALL BE BROUGHT TO THE ATTENTION OF THE BUILDING OFFICIAL AND TO THE REGISTERED DESIGN PROFESSIONAL IN RESPONSIBLE CHARGE PRIOR TO THE COMPLETION OF THAT PHASE OF THE WORK. A FINAL REPORT DOCUMENTING REQUIRED SPECIAL INSPECTIONS AND CORRECTION OF ANY DISCREPANCIES NOTED IN THE INSPECTIONS SHALL BE SUBMITTED AT A POINT IN TIME AGREED UPON PRIOR TO THE START OF WORK BY THE APPLICANT AND THE BUILDING OFFICIAL.
- 5. STATEMENT OF SPECIAL INSPECTION THE FOLLOWING SECTIONS IDENTIFY THE REQUIRED MATERIALS, SYSTEMS, COMPONENTS AND WORK TO BE SPECIAL INSPECTED AND TESTED: A. SOILS

VERIFICATION AND INSPECTION TASK		PERIODICALLY DURING TASK LISTED
VERIFY THE MATERIALS BELOW SLABS AND FOUNDATIONS ARE ADEQUATE TO ACHIEVE THE DESIGN BEARING CAPACITY.	-	x
VERIFY EXCAVATIONS ARE EXTENDED TO PROPER DEPTH AND REACH PROPER MATERIAL.	-	x
3. PERFORM CLASSIFICATION AND TESTING OF COMPACTED FILL MATERIALS.	-	x
4. VERIFY USE OF PROPER MATERIALS, DENSITIES AND LIFT THICKNESSES DURING PLACEMENT AND COMPACTION OF COMPACTED FILL.	х	-
 PRIOR TO PLACEMENT OF COMPACTED FILL, OBSERVE SUBGRADE AND VERIFY THAT SITE HAS BEEN PREPARED PROPERLY. 	-	Х

B. CONCRETE:

VERIFICATION AND INSPECTION TASK	CONTINUOUS	PERIODIC
INSPECTION OF REINFORCING STEEL, INCLUDING PRESTRESSING TENDONS, AND PLACEMENT.	-	Х
INSPECTION OF REINFORCING STEEL WELDING IN ACCORDANCE WITH TABLE 1705.2.2, ITEM 2b.	-	-
INSPECTION OF ANCHORS CAST IN CONCRETE WHERE ALLOWABLE LOADS HAVE BEEN INCREASED OR WHERE STRENGTH DESIGN IS USED.	-	Х
4. VERIFYING USE OF REQUIRED MIX DESIGN.	-	Х

- C. PLUMBING. MECHANICAL AND ELECTRICAL COMPONENTS: PERIODIC INSPECTION FOR:
- a. ANCHORAGE OF ELECTRICAL EQUIPMENT FOR EMERGENCY AND STANDBY POWER
- b. INSTALLATION AND ANCHORAGE OF PIPING SYSTEMS DESIGNED TO CARRY HAZARDOUS MATERIALS AND THEIR ASSOCIATED MECHANICAL UNITS.
- c. INSTALLATION AND ANCHORAGE OF DUCTWORK DESIGNED TO CARRY HAZARDOUS MATERIALS.



Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Re-Scope 1:2

A. Eckhart, P.E. E. Swanson

Matt Miller, P.E. Tyler Jirges, P.E. gned By Tyler Jirges, P.E.







Bozeman, MT 59718 Phone (406) 284-2110

City Of Missoula

Project Title

Garden City Compost Facility Improvements

Sheet Title

Structural Notes

03.30 CAST-IN-PLACE:

- 1. CONCRETE CONSTRUCTION & MATERIALS SHALL COMPLY WITH THE STANDARDS SPECIFIED IN AMERICAN CONCRETE INSTITUTE (ACI) 318-19, "BUILDING CODE REQUIREMENTS FOR STRUCTURAL CONCRETE" FOR BUILDING STRUCTURES. ENVIRONMENTAL STRUCTURES SHALL COMPLY WITH ACI 350-20, "CODE REQUIREMENTS FOR ENVIRONMENTAL ENGINEERING CONCRETE STRUCTURES".
- CONCRETE
- 3. CONCRETE STRENGTH DESIGN REQUIREMENTS SHALL BE AS FOLLOWS:

CONCRETE MIX DESIGNS							
COMPONENT	f'c at 28 Max w/cm	Air Content	Max Aggregate	Exposure Classes*			
COMIT GIVEN	Days (psi)	Ratio	(%)	Size	F	S	С
Footings	4500	0.42	4.5	1	F1	S0	C1
Foundation Walls/Push Walls	4500	0.42	6	1	F2	S0	C1
Slab-on-grade (exterior)	4500	0.42	3	1	F2	S0	C1

SEE SPEC. SECTION 03 30 00 FOR MIX DESIGN REQUIREMENTS.

- REINFORCEMENT MATERIALS
- A. DEFORMED REINFORCING BARS SHALL CONFORM TO:
- a. ASTM A615 STANDARD REINFORCING, GRADE 60; GRADE 40 SHALL BE ALLOWED FOR #3 AND SMALLER BARS
- b. ASTM A706 REINFORCING TO BE WELDED, GRADE 60
- 5. CONSTRUCTION REQUIREMENTS
- A. LOCATION OF CONSTRUCTION JOINTS NOT SHOWN ON THE DRAWINGS SHALL BE APPROVED BY THE ENGINEER. CONSTRUCTION JOINTS SHALL NOT BE PLACED AT LOCATION OTHER THAN THOSE SHOWN ON DRAWINGS UNLESS PRIOR WRITTEN APPROVAL IS OBTAINED FROM THE ENGINEER.
- B. FINISH ALL CONCRETE IN ACCORDANCE WITH SPEC. SECTION 03 30 00.
- C. REINFORCING BARS SHALL NOT BE WELDED UNLESS SPECIFICALLY SHOWN ON DRAWINGS.
- D. FIELD BENDING OF REINFORCEMENT PARTIALLY EMBEDDED IN CONCRETE SHALL NOT BE PERMITTED. EXCEPT AS SHOWN IN THE CONSTRUCTION DOCUMENTS.
- E. OFFSET BARS SHALL BE BENT BEFORE PLACEMENT IN THE FORMS.
- F. ALL REINFORCEMENT SHALL BE BENT COLD, AND SHALL BE BENT ONLY ONCE AT THE SAME LOCATION. ALL REINFORCEMENT SHALL BE SHOP BENT, UNLESS OTHERWISE PERMITTED BY THE EOR.
- G. CONCRETE COVER FOR CAST-IN-PLACE NONPRESTRESSED CONCRETE MEMBERS
- a. CAST AGAINST AND PERMANENTLY IN CONTACT WITH GROUND: COVER = 3"
- b. FORMED CONCRETE EXPOSTED TO EARTH, LIQUID, WEATHER OR BEARING ON WORK MAT OR SLABS SUPPORTING EARTH COVER:
- c. CONDITIONS NOT COVERED BY "a" OR "b" SECTION PREVIOUSLY:

SLABS, JOISTS, & WALLS: No. 11 BAR & SMALLER - COVER = 3/4"

No. 14 & No. 18 BARS - COVER = 1-1/2"

BEAMS, COLUMNS:

STIRRUPS, TIES, SPIRALS, HOOPS - COVER = 1-1/2" PRIMARY REINF. - COVER = 2"

- H. REINFORCING SHALL BE ACCURATELY FORMED TO DIMENSIONS INDICATED IN DRAWINGS AND PER BENDING DETAILS- SEE DETAIL 5/S10-1.
- NO PLICING SHALL BE PERMITTED EXCEPT AS NOTED ON DRAWINGS. WHERE PERMITTED SPLICES MAY BE MADE BY CONTACT LAPS - SEE LAP DETAIL 3/S10-1.

03.30 CAST-IN-PLACE CONTINUED:

- 6. PLACEMENT TOLERANCE
- a. PLACEMENT OF NONPRESTRESSED REINFORCEMENT
 - WHEN MEMBER DEPTH (OR THICKNESS) IS 4" OR LESS: ±1/4"
 - WHEN MEMBER DEPTH (OR THICKNESS) IS OVER 4" AND NOT OVER 12": ±3/8" - WHEN MEMBER DEPTH (OR THICKNESS) IS OVER 12": ±1/2"
 - b. CONCRETE COVER MEASURED PERPENDICULAR TO CONCRETE SURFACE
 - WHEN MEMEBER DEPTH (OR THICKNESS) IS 12" OR LESS: -3/8"
 - WHEN MEMEBER DEPTH (OR THICKNESS) IS OVER 12": -1/2"
 - REDUCTION IN COVER SHALL NOT EXCEED 1/3 THE SPECIFIED CONCRETE COVER
 - REDUCTION IN COVER TO FORMED SOFFITS SHALL NOT EXCEED 1/4"
 - c. VERTICAL DEVIATION FOR SLAB-ON-GROUND REINFORCEMENT: ±3/4"
 - d. CLEARANCE BETWEEN REINFORCEMENT OR BETWEEN REINFORCEMENT AND **EMBEDMENT**
 - ONE-QUARTER SPECIFIED DISTANCE NOT TO EXCEED: ±1"
 - DISTANCE BETWEEN REINFORCEMENT SHALL NOT BE LESS THAN THE GREATER OF THE BAR DIAMETER OR 1" FOR UNBUNDLED BARS
 - FOR BUNDLED BARS, THE DISTANCE BETWEEN BUNDLES SHALL NOT BE LESS THAN THE GREATER OF 1" OR A BAR DIAMETER DERIVED FROM THE EQUIVALENT TOTAL AREA OF ALL BARS IN THE BUNDLE
 - e. SPACING OF NONPRESTRESSED REINFORCEMENT, MEASURED ALONG A LINE PARALLEL TO THE SPECIFIED SPACING
 - EXCEPT AS NOTED BELOW: ±3"
 - STIRRUPS. THE LESSOR OF ±3" OR ±1" PER FT OF BEAM DEPTH
 - TIES, THE LESSER OF ±3" OR ±1" PER FT OF LEAST COLUMN WIDTH
 - THE TOTAL NUMBER OFBARS SHALL NOT BE FEWER THAN THAT SPECIFIED
 - f. LONGITUDINAL LOCATION OF BENDS IN BARS AND ENDS OF BARS
 - AT DISCONTINUOUS ENDS OF CORBELS AND BRACKETS: ±1/2"
 - AT DISCONTINUOUS ENDS OF OTHER ELEMENTS: ±1"
 - AT OTHER LOCATIONS: ±2"
 - g. EMBEDDED LENGTH OF BARS AND LENGTH OF BAR LAPS
 - #3 THROUGH #11 BAR SIZES: -1"
 - #14 AND #18 BARS: -2"
 - h. PLACEMENT OF SMOOTH ROD OR PLATE DOWELS IN SLAB-ON-GROUND
 - CENTERLINE OF DOWEL. VERTICAL DEVIATION MEASURED FROM BOTTOM OF CONCRETE SLAB AT THE JOINT FOR ELEMENT DEPTH 8" OR LESS: ±1/2" WHEN ELEMENT DEPTH IS OVER 8": ±1"
 - SPACING OF DOWELS, MEASURED ALONG A LINE PARALLEL TO THAT SPECIFIED SPACING: ±3"
 - THE TOTAL NUMBER OF DOWELS SHALL NOT BE FEWER THAN THAT SPECIFIED
 - CENTERLINE OF DOWEL WITH RESPECT TO A HORIZONTAL LINE THAT IS
 - PERPENDICULAR TO THE PLANE ESTABLISHED BY THE JOINT
 - 1. HORIZONTAL DEVIATION: ±1/2"
 - 2. VERTICAL DEVIATION: ±1/2" i. ANCHOR BOLTS IN CONCRETE
 - TOP OF ANCHOR BOLTS SPECIFIED ELEVATION
 - 1. VERTICAL DEVIATION: ±1/2"
 - CENTERLINE OF INDIVIDUAL ANCHOR BOLTS FROM SPECIFIED LOCATION
 - 1 HORIZONTAL DEVIATION
 - A. FOR 3/4" AND 7/8" BOLTS: ±1/4"
 - B. FOR 1". 1-1/4" AND 1-1/2" BOLTS: ±3/8"
 - C. FOR 1-3/4", 2", AND 2-1/2" BOLTS: ±1/2"

05.05 19 POST-INSTALLED ANCHORS:

- I. POST-INSTALLED ANCHORS IN CONCRETE SHALL BE IN ACCORDANCE WITH THESE NOTES UNLESS NOTED DIFFERENTLY IN PLANS AND DETAILS. SEE PLANS AND DETAILS FOR ANCHOR TYPE, SIZE, AND SPACING. POST-INSTALLED ANCHORS SHALL NOT BE USED IN PLACE OF SPECIFIED CAST-IN-PLACE ANCHORS SPECIFIED IN DRAWINGS, UNLESS SPECIFIED IN PLANS OR DETAILS, OR WRITTEN APPROVAL BY ENGINEER OF RECORD.
- QUALITY ASSURANCE: INSTALLER FOR DRILLED-IN ANCHORS SHALL HAVE AT LEAST (3) YEARS OF EXPERIENCE PERFORMING SIMILAR INSTALLATIONS.
- STORE ANCHORS AND INJECTION ADHESIVE IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
- . INSTALLATION OF POST-INSTALL ANCHORS SHALL BE IN ACCORDANCE WITH MANUFACTURER'S WRITTEN INSTRUCTIONS.
- INSTALLATION OF ADHESIVE ANCHORS THAT ARE TO BE UNDER SUSTAINED TENSION LOADING IN HORIZONTAL TO VERTICALLY OVERHEAD ORIENTATION SHALL BE DONE BY A CERTIFIED ADHESIVE ANCHOR INSTALLER (AAI) AS CERTIFIED THROUGH ACI AND IN ACCORDANCE WITH ACI 318.
- ADHESIVE ANCHORS SHALL BE INSTALLED IN CONCRETE HAVING A MINIMUM AGE OF 21 DAYS AT TIME OF ANCHOR INSTALLATION. FOR INSTALLATIONS SOONER THAN 21 DAYS CONSULT ADHESIVE MANUFACTURER.
- EXISTING REINFORCING SHALL NOT BE DAMAGED DURING INSTALLATION OF ANCHOR.
- ALL MISDRILLED OR UNACCEPTABLE HOLES SHALL NOT BE USED.
- REMOVE AND REPLACE MISPLACED OR MALFUNCTIONING ANCHORS. FILL EMPTY ANCHOR HOLES AND PATCH FAILED ANCHOR LOCATIONS WITH HIGH-STRENGTH NON-SHRINK GROUT.

05.05 FABRICATED METAL WORK:

- 1. STEEL SHAPES SHALL CONFORM TO THE FOLLOWING MATERIAL GRADES:
- A. MISC SHAPES INCLUDING
- B. EMBED PLATS, EMBED ANGLES, ETC: A36
- C. ASCE RAIL: 55Q
- D. PUSH WALL PLATES AT BIOSOLIDS AND PRE-COMPOST MIXING BINS: A400
- BOLTS SHALL BE HIGH STRENGTH BOLTS CONFORMING TO THE FOLLOWING ASTM STANDARDS EXPECT WHERE NOTED OTHERWISE:
- A. UNLESS NOTED OTHERWISE: A325-N
- B. MACHINE BOLTS (MB) AND ANCHOR BOLTS (AB)
- a. STAINLESS STÈEL MB AND AB: F593. TYPE 316
- b. STEEL MB: A307
- c. STEEL AB: F1554, GRADE 55
- 3. ITEMS EMBEDDED IN CONCRETE SHALL BE CLEAN AND FREE OF OIL, DIRT, AND PAINT.

31.00 EARTHWORK:

- 1. THE FOUNDATION DESIGN IS BASED UPON GEOTECHNICAL RECOMMENDATIONS CONTAINED IN THE REPORT, "GARDEN CITY COMPOST GEOTECHNICAL REPORT", BY "PIONEER GEOTECHNICAL SERVICES". DATED FEB. 9. 2024. RECOMMENDATIONS PROVIDED BY THIS REPORT SHALL BE FOLLOWED IN ADDITION TO SPECIFICATIONS AND DETAILS IN DRAWINGS.
- 2. REGISTERED PROFESSIONAL GEOTECHNICAL ENGINEER SHALL JUDGE SUITABILITY OF UNDERLYING MATERIAL TO SUPPORT FOUNDATIONS AND SHALL APPROVE BEARING MATERIAL BEFORE FOUNDATION INSTALLATION.
- ALL FILL MATERIALS SHALL BE COMPACTED IN ACCORDANCE WITH RECOMMENDATIONS OF GEOTECHNICAL REPORT, WHEN PRODUCED FOR THE PROJECT, BUT NOT LESS THAN THE FOLLOWING:
- A. STRUCTURAL FILL: 95% OF *MAX DRY DENSITY.
- B. SOILS BENEATH SLABS: 95% OF *MAX DRY DENSITY
- C. BACKFILL: 95% OF *MAX DRY DENSITY
- *ASTM D698 STANDARD PROCTOR
- a. STAINLESS STEEL MB AND AB: F593, TYPE 316
- b. STEEL MB: A307
- c. STEEL AB: F1554, GRADE 55
- ALL FOOTINGS/SLABS SHALL BEAR ON COMPACTED STRUCTURAL FILL, WHICH IS IN TURN SUPPORTED BY FIRM NATIVE SOIL SUBGRADE (POORLY GRADED GRAVELS WITH SAND AND COBBLES).
- ALL PERIMETER FOOTINGS AND EXTERIOR FOOTINGS SHALL BEAR A MINIMUM OF 42IN BELOW FINISH GRADE, U.N.O.
- 3. CONTRACTOR IS RESPONSIBLE FOR THE SAFETY OF EXCAVATIONS, PROTECTION OF EXISTING UTILITIES AND STRUCTURES, ETC. WHETHER INDICATED OR NOT.
- CONTRACTOR SHALL PROVIDE CONTINUOUS SITE DRAINAGE BY A MECHANICAL METHOD TO CONTROL SURFACE AND UNDERGROUND WATER AS REQUIRED TO MAINTAIN A DRY WORKING
- 8. COORDINATE UNDER GROUND UTILITIES AND PIPING WITH MECHANICAL, PLUMBING AND CIVIL DRAWINGS.
- THE TOP SURFACE OF FOOTINGS SHALL BE LEVEL. FOOTING SHALL BE STEPPED PER STANDARD DETAIL WHERE IT IS NECESSARY TO CHANGE THE TOP SURFACE OF THE FOOTING.
- IO.PLACE BACKFILL AT EQUAL HEIGHT LIFTS EACH SIDE OF BURIED WALLS TO PREVENT UNBALANCED EARTH PRESSURES ACTING ON WALL. I 1.DO NOT BACKFILL EARTH RETAINING WALLS UNTIL SPECIFIED STRENGTH IS ATTAINED.



Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Re-Scope

1:2 A. Eckhart, P.E.

E. Swanson Matt Miller, P.E.

Tyler Jirges, P.E. gned By Tyler Jirges, P.E.



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303



602 S. Ferguson Ave. STE 5 Bozeman, MT 59718 Phone (406) 284-2110

City Of Missoula

Garden City Compost Facility Improvements


Sheet Title

Structural Notes Continued

PLAN OR SECTION VIEW


Wall/Footing Construction Joint NO SCALE

• KEYWAY MAY BE OMITTED IN FOOTING CONSTRUCTION JOINTS.




Form Snap-Tie Hole 3

- THE SPACING OF FORM TIES ON EXPOSED PORTIONS OF WALLS SHALL BE APPROXIMATELY EQUAL HORIZONTALLY AND VERTICALLY AND SHALL BE UNIFORM IN EACH DIRECTION.
- DRY PACK METHOD SHALL BE AS SPECIFIED USING STEEL TOOLS.



PLAN VIEW

Wall Expansion Joint Treatment 4 NO SCALE




PLAN VIEW

Wall Vertical Control/Contraction Joint 2



- 1. FOR WALLS WITH THICKNESS OF 10" THROUGH 24"
- 2. 1" DIA, x 3'-0" SMOOTH COATED BAR DOWELS, LOCATE AT 1'-0" MAX FROM T AND B OF WALL AND AT 2'-0" MAX SPACING. ALIGN AND TIE-IN-PLACE TO REINFORCEMENTS. COATING SHALL CONSIST OF A CORROSION RESISTANT COATING PLUS A LUBRICANT COATING AS SPECIFIED.
- 3. 1" ID x 2" PLASTIC CAP WITH 1" POLYSTYRENE BETWEEN END OF DOWEL AND END CAP. TAP TO BAR FOR WATERTIGHT SEAL.
- 4. MAXIMUM SPACING FOR WALL VERTICAL CONTROL/CONTRACTION JOINTS IS 40' (TYP.).



Wall Vertical Expansion Joint 5



- 1. FOR WALLS WITH THICKNESS OF 10" THROUGH 24"
- 2. 1" DIA. x 3'-0" SMOOTH COATED BAR DOWELS. LOCATE AT 1'-0" MAX FROM T AND B OF WALL AND AT 2'-0" MAX SPACING. ALIGN AND TIE-IN-PLACE TO REINFORCEMENTS. COATING SHALL CONSIST OF A CORROSION RESISTANT COATING PLUS A LUBRICANT COATING AS SPECIFIED.
- 3. 1" ID x 2" PLASTIC CAP WITH 1" POLYSTYRENE BETWEEN END OF DOWEL AND END CAP. TAP TO BAR FOR WATERTIGHT SEAL.



Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE
	1	

Re-Scope 1:2

A. Eckhart, P.E. E. Swanson Matt Miller, P.E. Tyler Jirges, P.E.

signed By Tyler Jirges, P.E.

1064 N. Warren Helena, MT 59601



602 S. Ferguson Ave. STE 5 Bozeman, MT 59718 Phone (406) 284-2110

City Of Missoula

Project Title


Garden City Compost **Facility Improvements**


Structural **Details**

SECTION VIEW

Slab Control/Contraction Joint

- 1. AT CONTRACTOR'S OPTION, CONTROL JOINTS MAY BE FORMED OR SAWED. JOINTS MUST BE SAWN BETWEEN 12 AND 24 HOURS AFTER CONCRETE HAS BEEN PLACED.
- 2. DESIGN OF DIAMOND PLATE DOWEL SPACING TO BE SUBMITTED TO EOR FOR REVIEW.
- 3. AT CONTRACTOR'S OPTION, DIAMOND PLATE DOWELS MAY BE SUBSTITUED WITH 3/4"x10" SMOOTH DOWELS SPACED AT 12" O.C., CENTERED IN DEPTH OF SLAB, HALF DOWEL ON EITHER SIDE OF JOINT SHALL BE COATED WITH LIQUID ASPHALT MC-250, ROAD TAR RT-6, OR APPROVED EQUAL TO REDUCE BOND WITH CONCRETE ON ONE SIDE OF JOINT.





3/8" RADIUS TOOLED EDGE (TYP.)-

AT JOINT (TYP.)

NO SCALE

3/4"

SECTION VIEW

Footing Construction/Expansion Joint 2

—2" CLEAR

STOP SLAB REINFORCING-

PREMOLDED JOINT FILLER,

BITUMINOUS TYPE, ATTACH WITH 8d

GALVANIZED NAILS AT 1'-0" SPACING

SLAB

THICKNESS

EMBEDDED IN FIRST SLAB POUR.

SINGLE REINFORCING MAT

Typical Wall Corner and Intersection Reinforcing 3

- SPACING SEE PLANS. ALL HORIZONTAL REINFORCING AT CORNERS AND INTERSECTIONS SHALL BE FABRICATED AND INSTALLED WITH SPLICES LOCATED WHERE SHOWN
- 3. EXCEPT WHERE OTHERWISE SHOWN ON THE DRAWINGS, THE LENGTH INDICATED AS "NOTE 3" SHALL BE THE LESSER OF L/4, 10 FEET, OR 1.0 TIMES THE HEIGHT OF THE WALL, EXCEPT THAT IN NO CASE SHALL IT BE LESS THAN 2 FEET.
- 4. L = LENGTH OF WALL PARALLEL TO THE BAR LENGTH IN QUESTION.
- 5. EXCEPT WHERE OTHERWISE SHOWN ON THE DRAWINGS, THE LENGTH INDICATED AS "NOTE 5" SHALL BE EQUAL TO ONE "LAP LENGTH" AS REQUIRED BY THE GENERAL
- 6. UNLESS OTHERWISE NOTED, "B" AND "C" BARS ARE THE SAME SIZE AND SPACING AND, "F" AND "G" BARS ARE THE SAME SIZE AND SPACING.
- 7. HORIZONTAL WALL REINFORCING BETWEEN CORNERS AND INTERSECTIONS AS SHOWN ON WALL SECTIONS, LAP WITH CORNER AND INTERSECTION REINFORCING.
- 8. TYPICAL HORIZONTAL WALL REINFORCING AS SHOWN ON DRAWINGS, LAP WITH CORNER AND INTERSECTION REINFORCING.



Revision	Date	Ву
Final	4/2/25	AE
Re-Scop	e 5/7/25	AE

Re-Scope 1:2

A. Eckhart, P.E. E. Swanson Matt Miller, P.E. Tyler Jirges, P.E.

Tyler Jirges, P.E.



1064 N. Warren Helena, MT 59601



602 S. Ferguson Ave. STE 5 Bozeman, MT 59718 Phone (406) 284-2110

City Of Missoula

Garden City Compost Facility **Improvements**

Structural Details


- 1. TYPICAL HORIZONTAL WALL CORNER AND INTERSECTION REINFORCING LAYOUT IS SHOWN TO AVOID CONGESTION AND PERMIT PROPER PLACEMENT, FOR SIZE AND REGARDLESS OF BAR SIZE AND SPACING.
- 2. WHERE THE CORNER OR INTERSECTION REINFORCING SIZE AND SPACING IS NOT SHOWN, NOTED OR TABULATED ON THE PLANS. THE SIZE AND SPACING SHALL BE THE SAME AS THE WALL HORIZONTAL REINFORCING SHOWN ON THE WALL SECTIONS OR AS NOTED FOR THE REINFORCING BETWEEN THE CORNERS OR INTERSECTIONS.
- STRUCTURAL NOTES. USE THE LAP LENGTH AS REQUIRED FOR THE SMALLER OF THE TWO REINFORCING BARS BEING SPLICED.

PLAN VIEW

Concrete Corner Armor Angle 1 NO SCALE

NOTES


- PAINT ASSEMBLY WITH SYSTEM NO. 4 AFTER FABRICATION.
- INSTALL BOTTOM OF ANGLE AT TOP OF SLAB ELEVATION.
- PROVIDE (1) VERTICAL ROW OF 3/16"Ø HOLES ALONG EACH ANGLE LEG FOR ATTACHMENT OF ANGLE TO FORMWORK.



Blower/Fan Concrete Pedestal 3 NO SCALE ~

...___

- BARS SHALL BE PLACED ON 8" CENTERS AROUND PAD.
- ANCHOR BOLTS SHALL BE SIZED AND INSTALLED PER MANUFACTURER'S RECOMMENDATIONS.
- 3" MINIMUM COVER FOR ALL REBAR
- THE TAIL IN THE VERTICAL BARS SHALL BE LOCATED IN THE MIDDLE OF THE SLAB ON GRADE.
- REBAR SHALL BE TIED TOGETHER AT ALL CROSSINGS.




PLAN VIEW

Wall Construction Joint Spacing 2 NO SCALE 2

NOTES:

- COORDINATE CONSTRUCTION JOINT LOCATIONS AND TIME BETWEEN CONCRETE POURS WITH PLANS AND PROJECT SPECIFICATIONS.
- LOCATE WALL CONSTRUCTION JOINTS AS SHOWN, UNLESS INDICATED OTHERWISE.



Wall/Footing Keyway Joint Detail 4 NO SCALE



Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

vision		
	Scope	
t Scale		
	:2	
awn By		
A. Eck	hart, P.	E.

E. Swanson
proved By
Matt Miller, P.E.
hecked By
Tyler Jirges, P.E.
esigned By
Tyler Jirges, P.E.



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303



602 S. Ferguson Ave. STE 5 Bozeman, MT 59718 Phone (406) 284-2110

Owner

City Of Missoula


Project Title

Garden City Compost Facility Improvements

neet Title

Structural Details

Sheet



STIF	RRUP (TI	ES SIMILAR) ST DIMENSIO	IRRUP AND TIE	ноок
BAR SIZE		90° HOOK	135° H	ООК
No.	D,* in.	HOOK A OR G,	HOOK A OR G,	H APPROX.,
		ft-in.	ft-in	ft-in
#3	1 ½	4	4	2 1/2
#4	2	4 ½	4 ½	3
#5	$2\frac{1}{2}$	6	5 ½	3 3/4
#6	4 ½	1-0	8	4 ½
#7	5 ½	1-2	9	5 ½
#8	6	1-4	10 ½	6

135° SEISM	IIC STIR	RUP/TIE HOOK I	DIMENSIONS
BAR SIZE		135° H	ООК
No.	D,* in.	HOOK A OR G, ft-in	H APPROX., ft-in
#3	1 ½	4 1/4	3
#4	2	4 ½	3
#5	$2\frac{1}{2}$	5 ½	3 3/4
#6	4 ½	8	4 ½
#7	5 ½	9	5 ½
#8	6	10 ½	6

		NDED ENI BEND D		•
BAR		135° H	ООК	90° HOOK
SIZE No.	D,* in.	A OR G, ft-in	J, ft-in	A OR G, ft-in.
#3	2 1/4	5	3	6
#4	3	6	4	8
#5	3 ³ / ₄	7	5	10
#6	4 ½	8	6	1-0
#7	5 ½	10	7	1-2
#8	6	11	8	1-4
#9	9 ½	1-3	11 ³ / ₄	1-7
#10	10 ³ / ₄	1-5	1-1 1/4	1-10
#11	12	1-7	1-2 3/4	2-0
#14	18 ¹ / ₄	2-3	1-9 3/4	2-7
#18	24	3-0	2-4 ½	3-5

Standard Rebar Hooks 1

BAR SIZE "db"		f'c =	3500	PSI			f'c =	4000	PSI			f'c =	4500	PSI			f'c =	5000) PSI	
(GRADE 60)	L _d	L _t	L _{sb}	L _{sbt}	L _{dh}	L _d	L _t	L _{sb}	L _{sbt}	L _{dh}	L _d	Lt	L _{sb}	L _{sbt}	L _{dh}	L _d	L _t	L _{sb}	L _{sbt}	L _{dh}
#4	22"	29"	29"	38"	8"	19"	25"	25"	33"	7"	18"	24"	24"	31"	7"	17"	23"	23"	30"	6"
#5	28"	36"	36"	47"	10"	24"	31"	31"	41"	9"	23"	30"	30"	38"	8"	22"	28"	28"	37"	8"
#6	33"	43"	43"	56"	12"	29"	37"	37"	49"	10"	27"	35"	35"	46"	10"	26"	34"	34"	45"	9"
#7	48"	63"	63"	81"	14"	42"	54"	54"	71"	12"	40"	51"	51"	67"	11"	38"	49"	49"	64"	11'
#8	51"	67"	67"	86"	15"	48"	62"	62"	81"	14"	45"	59"	59"	77"	13"	43"	56"	56"	73"	12'
#9	58"	76"	76"	98"	16"	54"	70"	70"	91"	15"	51"	66"	66"	86"	15"	48"	63"	63"	82"	14'


NOTES:

COURSINGS PER GEOTECHNICAL


DISTANCE FROM CONCRETE EDGE


- 1. ALL TABULATED VALUES REQUIRE CLEAR SPACING BETWEEN BARS ≥ 2*db & CLEAR COVER ≥ db (IF THESE CONDITIONS ARE NOT SATISFIED, MULTIPLY TABULATED VALUES BY 1.5)
- 2. L_d = TENSION DEVELOPMENT LENGTH
- 3. $L_t = DEVELOPMENT LENGTH FOR "TOP" BARS IN TENSION.$
- 4. $L_{\rm sb}$ = TENSION LAP SPLICE LENGTH FOR BARS OTHER THAN "TOP" BARS ("CLASS B")
- 5. L_{sbt} = TENSION LAP SPLICE LENGTH OF "TOP" BARS.
- 6. L_{dh} = TENSION HOOK DEVELOPMENT LENGTH (SIDE COVER $\geq 2\frac{1}{2}$ ", END COVER ≥ 2 ").
- 7. "TOP" BARS = REINFORCEMENT WITH > 12" OF FRESH CONCRETE CAST BELOW.





Supplemental Reinf. At Discontinuous Control Joints







-		
Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Re-Scope

1:2 A. Eckhart, P.E.

E. Swanson Matt Miller, P.E.

Tyler Jirges, P.E. Tyler Jirges, P.E.

1064 N. Warren Helena, MT 59601 Phone (406) 449-3303




602 S. Ferguson Ave. STE 5 Bozeman, MT 59718 Phone (406) 284-2110

City Of Missoula

Garden City Compost Facility Improvements

Structural **Details**





Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Revision Re-Scope Plot Scale

> A. Eckhart, P.E. wn By E. Swanson

Matt Miller, P.E.
Checked By
Tyler Jirges, P.E.
Designed By
Tyler Jirges, P.E.

gineer

Anderson~Montgomery

1064 N. Warren Helena, MT 59601 Phone (406) 449-3303



602 S. Ferguson Ave. STE 5 Bozeman, MT 59718 Phone (406) 284-2110

Owner

City Of Missoula


Project Title

Garden City Compost Facility Improvements

Sheet Title

Structural Details

heet





Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Revision Re-Scope

Scale

rawn By A. Eckhart, P.E.

Drawn By
E. Swanson

Approved By
Matt Miller, P.E.
Checked By
Tyler Jirges, P.E.

Designed By
Tyler Jirges, P.E.

AAA

1064 N. Warren Helena, MT 59601 Phone (406) 449-3303



602 S. Ferguson Ave. STE 5 Bozeman, MT 59718 Phone (406) 284-2110

Owner

City Of Missoula


Project Title

Garden City Compost Facility Improvements

Sheet Title

Structural Details

She



2. CONTROL JOINTS LOCATED WITHIN THE EQUIPMENT SLAB ARE ALLOWED TO BE

3. GENERAL CONTRACTOR SHALL SUBMIT A POUR SEQUENCE PLACEMENT PLAN TO

EITHER TOOLED OR SAWCUT, SEE SHEET S-10 FOR JOINT SPACING.

EOR FOR REVIEW PRIOR TO COMMENCEMENT OF CONSTRUCTION.



Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Revision Re-Scope
Plot Scale
1:2

A. Eckhart, P.E.

rawn By
E. Swanson

pproved By
Matt Miller, P.E.

Tyler Jirges, P.E.
ssigned By
Tyler Jirges, P.E.

Anderson~ Montgomery

1064 N. Warren Helena, MT 59601 Phone (406) 449-3303



602 S. Ferguson Ave. STE 5 Bozeman, MT 59718 Phone (406) 284-2110

Owner

City Of Missoula


Project Title


Garden City Compost Facility Improvements

Sheet Title

Overall Slab On Grade Plan

Sheet







Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

t Scale 1:2

A. Eckhart, P.E.

E. Swanson

Matt Miller, P.E.

Checked By
Tyler Jirges, P.E.

esigned By Tyler Jirges, P.E.

ingineer



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303



602 S. Ferguson Ave. STE 5 Bozeman, MT 59718 Phone (406) 284-2110

Owner

City Of Missoula


Project Title

Garden City Compost Facility Improvements

Sheet Title

Push Wall Section

She





Revision	Date	Ву				
Final	4/2/25	AE				
Re-Scope	5/7/25	AE				

A. Eckhart, P.E. E. Swanson

Tyler Jirges, P.E. Tyler Jirges, P.E.

1064 N. Warren Helena, MT 59601




02 S. Ferguson Ave. STE 5 Bozeman, MT 59718 Phone (406) 284-2110

City Of Missoula

Garden City Compost Facility Improvements

Biosolids Bin Details





Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

1:2 A. Eckhart, P.E.

E. Swanson Matt Miller, P.E.

Checked By
Tyler Jirges, P.E. esigned By Tyler Jirges, P.E.

1064 N. Warren Helena, MT 59601 Phone (406) 449-3303




602 S. Ferguson Ave. STE 5 Bozeman, MT 59718 Phone (406) 284-2110

City Of Missoula

Project Title

Garden City Compost Facility Improvements

Pre-Compost Containment Bin Slab **Details**





Revision	Date	Ву
Final	4/2/25	AE
Re-Scope	5/7/25	AE

Revision Re-Scope

Scale 1:2

wn By A. Eckhart, P.E.

E. Swanson
proved By
Matt Miller, P.E.

Checked By
Tyler Jirges, P.E.
Designed By

esigned By Tyler Jirges, P.E.

ingineer



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303



602 S. Ferguson Ave. STE 5 Bozeman, MT 59718 Phone (406) 284-2110

Owi

City Of Missoula


Project Title

Garden City Compost Facility Improvements

Sheet Title

Biosolids Bin Wall Elevations

She



Revision	Date	Ву				
Final	4/2/25	AE				
Re-Scope	5/7/25	AE				

Re-Scope	5/7/25	AE				
evision						
Re-Scope						

l .	e-Scope
Plot Scale	
	1:2
Drawn By	

A. Eckhart, P.E. E. Swanson Matt Miller, P.E.

hecked By
Tyler Jirges, P.E. signed By Tyler Jirges, P.E.



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303



602 S. Ferguson Ave. STE 5 Bozeman, MT 59718 Phone (406) 284-2110

City Of Missoula

Project Title

Garden City Compost Facility Improvements

Biosolids & **Pre-Compost Mixing Bin Details**

PAINE	L SCHEDULE			LOCATIO				AIC RATING: MOUNTING:		14K SURFACE			PANEL NAME:	MDP	
CKT		PDF	AKER	REF.			LOAD TYPE (JUNI ACE			PANEL DATA		
	DESCRIPTION				LTG.	REC'S	MOTOR	VA) EQUIP	HEATING	COOLING		AMPS	AMPERAGE:	400	
NO. 1	SPARE	60	POLE 3	NOTE	LIG.	REUS	MOTOR	EQUIP	HEATING	COOLING	VA	0.0	VOLTAGE:	277/480	
3	SPARE	**	*										PHASE:	3	
	-	**	*									0.0	-		
5		_										0.0	WIRE:	4	
7	SPARE	20	3									0.0	MAINS		REF. NOTE
9	-	**	*									0.0	-	400A MCB	
11	-	_					1.010				1.010	0.0	LUGS ONLY	-	
13	LIFT STATION	30	3				4,210				4,210	15.2	GROUND BUSS		
15	-	**	*				4,210				4,210	15.2	EQUIPMENT:	YES	
17	-	**	*				4,210				4,210	15.2	ISOLATED:	-	
19	PANEL C1	40	2		300	360	1,440	550	0	0	2,650	9.6	NEUTRAL BUSSING		
21		**	*		0	1,080	1,440	2,400	0	0	4,920	17.8	100%	YES	
23	SPARE	20	1								0	0.0	200%	-	
25	SPARE	20	3								0	0.0	BUSSING		
27	-	**	*								0	0.0	COPPER:	YES	
29	-	**	*								0	0.0	ALUMINUM:	-	
											0	0.0	TOP FEED:	-	
											0	0.0	BOTTOM FEED:	-	
											0	0.0	FEED THRU LUGS:	-	
											0	0.0	SUB FEED LUGS:	-	
											0	0.0	CONNECTED TOTA	_S	
											0	0.0	(INCLUDES FEED-T		RIBUTION)
						1	1						LOAD	KVA	AMPS
2	BAY 1-6 DRIVE CABINET	100	3				18,268				18,268	65.9	LIGHTING:	0.3	0.4
4	-	**	*				18,268				18,268	65.9	RECEPTACLES:	1.4	1.7
6		**	*				18,268				18,268	65.9	MOTOR:	253.0	304.3
8	BAY 7-12 DRIVE CABINET	100	3				18,268				18,268	65.9	EQUIPMENT:	3.0	3.5
10	BAT 7-12 DRIVE CABINET	**	*				18,268				18,268	65.9	HEATING:		
	-	**	*				18,268				18,268		-	0.0	0.0
12			-				42,627				42,627	65.9	COOLING:	0.0	0.0
14	BIOFILTER DRIVE CABINET	225	3									153.9			
16	-						42,627				42,627	153.9	TOTALS	257.7	310.0
18	-	**	*				42,627				42,627	153.9	_		
20	225/3 SPACE										0	0.0	PHASE	KVA	AMPS
22	-										0	0.0	A:	86.0	310.6
24	-										0	0.0	B:	88.3	318.7
26	225/3 SPACE										0	0.0	C:	83.4	301.0
28	-										0	0.0	TOTAL	257.7	
30	-										0	0.0			
											0	0.0	FEEDER DEMAND T	OTALS	
											0	0.0	LOAD	KVA	AMPS
											0	0.0	LIGHTING:	0.4	0.5
											0	0.0	RECEPTACLES:	1.4	1.7
											0	0.0	MOTOR:	253.0	304.3
											0	0.0	EQUIPMENT:	3.0	3.5
REFER	ENCE NOTES:	_				1		1			-		HEAT/COOL:	0.0	0.0
1	21.02.10.120.												LARGEST MOTOR:	0.0	0.0
2													TOTAL	257.8	310.0
4													DATE:		05/29/25

	L SCHEDULE			LOCATION	ON:			AIC RATING:		10,000			PANEL NAME	: C1	
TA EN	IGINEERS			SOURCE	E:			MOUNTING:		SURFACE					
CKT		BRE	AKER	REF.			LOAD TYPE (VA)					PANEL DATA		
NO.	DESCRIPTION	AMP	POLE	NOTE	LTG.	REC'S	MOTOR	EQUIP	HEATING	COOLING	VA	AMPS	AMPERAGE:	100	
1	SPARE	20	1								0	0.0	VOLTAGE:	120/240	
3	RECEPTACLES	20	1			720					720	6.0	PHASE:	1	
5	RECEPTACLES	20	1			360					360	3.0	WIRE:	3	
7	DATA RACK	20	1			360					360	3.0	MAINS		REF. NO
9	BLOWER PANEL CONTROLS	20	1					200.00			200	1.7	CKT. BKR.	100 AMP M	СВ
11	BLOWER PANEL CONTROLS	20	1					200.00			200	1.7	LUGS ONLY		
13	BLOWER PANEL CONTROLS	20	1					200.00			200	1.7	GROUND BUSS		
15	SPARE	20	1								0	0.0	EQUIPMENT:	YES	
17	IRRIGATION WELL PUMP	25	2				1,440				1,440	12.0	ISOLATED:	-	
19	-	**	*				1,440				1,440	12.0	NEUTRAL BUSSIN		
21	SPACE										0	0.0	100%	YES	
23	SPACE										0	0.0	200%	-	
											0	0.0	BUSSING		
											0	0.0	COPPER:	-	
											0	0.0	ALUMINUM:	YES	
											0	0.0	TOP FEED:	-	
											0	0.0	BOTTOM FEED:	-	
											0	0.0	FEED THRU LUGS		
										-	0	0.0	SUB FEED LUGS:	-	
										+	0	0.0	CONNECTED TOT		
											0	0.0	(INCLUDES FEED-	KVA	AMPS
2	LIGHTING	20	1		300	T					300	2.5	LIGHTING:	0.3	1.3
4	GENERATOR BLOCK HEATER	20	1		300			1,200			1,200	10.0	RECEPTACLES:	1.4	6.0
6	GENERATOR BATTERY CHARGER	20	1					150			150	1.3	MOTOR:	2.9	12.0
8	AC UNIT	30	2					100			0	0.0	EQUIPMENT:	3.0	12.3
10	-	**	*								0	0.0	HEATING:	0.0	0.0
12	PLC PANEL	20	1					1,000			1,000	8.3	COOLING:	0.0	0.0
14	SPARE	20	1					,			0	0.0	-	0.0	0.0
16	SPARE	20	1								0	0.0	TOTALS	7.6	31.5
18	SPACE										0	0.0			
20	SPACE										0	0.0	PHASE	KVA	AMPS
22	SPACE										0	0.0	A:	2.7	22.1
24	SPACE										0	0.0	¬ _{В:}	4.9	41.0
26											0	0.0			
28											0	0.0	TOTAL	7.6	
30											0	0.0			
32											0	0.0	FEEDER DEMAND	TOTALS	
34											0	0.0	LOAD	KVA	AMPS
36											0	0.0	LIGHTING:	0.4	1.6
38											0	0.0	RECEPTACLES:	1.4	6.0
40											0	0.0	MOTOR:	2.9	12.0
40											0	0.0	EQUIPMENT:	3.0	12.3
42													HEAT/COOL:		0.0
	ENCE NOTES:												HEAT/COOL:	0.0	0.0
	ENCE NOTES:												LARGEST MOTOR		0.0

	LIC	SHTING FIXT	TURE SCHEDULE				
		FIXTURE				MOUN	TING
TYPE	DESCRIPTION	MFG.	CATALOG NUMBER	VOLTS	WATTS	TYPE	HEIGH"
L1	4000 LUMEN 4FT LED STRIP LIGHT	LITHONIA	CSS-L48-4000LM-MVOLT-40K-80CRI	120/277V	35.3	SURFACE	CEILING
W1	LED WALL LIGHT WITH PHOTOCELL	LITHONIA	WPX1-LED-PZ-40K-MVOLT-DDBXD-M4	120/277V			

	LEG	END	
SYMBOL	ABBREVIATIONS & MISCELLANEOUS	SYMBOL	DEVICES & POWER
a,b,c etc.	SWITCH DESIGNATION	\$	SWITCH - SPST
AC	ABOVE COUNTER	T	3 THREE WAY 4 FOUR WAY
AFF	ABOVE FINISHED FLOOR		C CALL IN
AG	ABOVE GROUND		D DIMMER K KEY OPERATED
BN1L-2,4,6			LV LOW VOLTAGE MC SPDT-MOMENTARY CONTACT
	CIRCUIT DESIGNATION, PANELBOARD BN1L, CIRCUITS 2, 4, 6		MLV SPDT-LOW VOLTAGE, MOMENTARY CONTAC
BOD	BOTTOM OF DEVICE		OS OCCUPANCY SENSOR P PILOT LIGHT
С	CONDUIT		WP WEATHERPROOF
COD	CENTER OF DEVICE	$\mid \rightarrow \mid$	RECEPTACLE - SIMPLEX
(E)	EXISTING	$\Rightarrow \Rightarrow$	RECEPTACLE - DUPLEX
EC	ELECTRICAL CONTRACTOR		GFI RECEPTACLE - DUPLEX (GROUND FAULT INTERRUPT D DEVICE RECEPT W/2 USB PORTS
GC	GENERAL CONTRACTOR		DC DROP CORD WP WEATHERPROOF
GND	GROUND		TR TAMPER RESISTANT S SURGE PROTECTED
GFI	GROUND FAULT CIRCUIT INTERRUPTER		IG ISOLATED GROUND
MC	MECHANICAL CONTRACTOR		FILLED CENTER INDICATES HOSPITAL GRADE EMERGENCY RECEPTACLE
MTS	MANUAL TRANSFER SWITCH	→ →	RECEPTACLE - DOUBLE DUPLEX
(N)	NEW		GFI RECEPTACLE - DOUBLE DUPLEX
NL	NIGHT LIGHT		- SAME INDICATORS AS SHOWN FOR DUPLEX
NWE	NORTHWESTERN ENERGY	₩	RECEPTACLE - 208V
UG	UNDERGROUND		D DRYER R RANGE
W/	WITH		W WELDER * NEMA CONFIGURATION AS NOTED
WP	WEATHER PROOF		
1/E5.2	INDICATES DETAIL 1 ON SHEET E5.2		FLOOR 208V RECEPTACLE
	SHEET WORK NOTE		FLOOR DUPLEX RECEPTACLE
$\stackrel{\langle 1 \rangle}{\widehat{}}$	SHEET WORK NOTE		FLOOR DOUBLE DUPLEX RECEPTACLE
	HOME RUN TO PANELS	0 1 0	J-BOX, J-BOX WALL MOUNTED, 4"x4"x2 1/8 " DEEP UNLES NOTED OTHERWISE
	CONDUIT CONCEALED IN CEILING OR WALL	PP	POWER POLE
	CONDUIT CONCEALED UNDER FLOOR		THERMOSTAT BY MC, INSTALLED AND CONNECTED BY E
	CIRCUIT, NUMBER OF HASH MARKS INDICATES NUMBER OF CONDUCTORS IN CABLE/RACEWAY. GROUND WIRE	- ⊕	THERMOSTAT BY MC, J-BOX & CONDUIT TO CEILING BY I
	NOT SHOWN BUT SHALL BE INCLUDED. NO HASH MARKS INDICATES 2 CONDUCTORS PLUS GROUND.	\$ _M	MANUAL MOTOR DISCONNECT/STARTER SWITCH
SYMBOL	LIGHTING	PB	PUSHBUTTON SWITCH SUPPLIED BY OTHERS, INSTALLE AND CONNECTED BY EC
	PENDANT OR SURFACE MOUNTED FLUORESCENT LIGHT	<u>DS</u>	DOOR SWITCH SUPPLIED BY OTHERS, INSTALLED AND CONNECTED BY EC
	FIXTURE, SIZE ON PLANS	TS	REMOTE TEST SWITCH
4_4	2 HEAD EMERGENCY LIGHT BATTERY PACK	PP	POWER PACK
2) (1 1 2 2)		<u> </u>	OCCUPANCY SENSOR
SYMBOL	COMMUNICATIONS		EMERGENCY PUSHBUTTON
⊢	DATA JACK, (1) CAT 6 JACK	R	RELAY
		<u>@</u>	PHOTOCELL
BENE	RAL NOTES (APPLICABLE TO ALL SHEETS)	+€0	PHOTOCELL, WALL MOUNTED
ALTHOUGH NO	T SHOWN, ALL RACEWAYS SHALL BE EQUIPPED WITH AN ROUNDING CONDUCTOR.	+ ● ●	SPECIAL PURPOSE CONNECTION, BOX INDICATES FLOO MOUNTING, WORK AS NOTED
	OR SIZE CALLED OUT IN THE HOME RUN SHALL BE CARRIED	Ø I	ELECTRIC MOTOR CONNECTION
	THE ENTIRE CONDUIT.		COMBINATION STARTER
	ICATE GENERAL DIRECTIONS AND ROUTES OF FEEDERS,		DISCONNECT SWITCH
	JITS, AND SERVICE CONDUCTOR SYSTEMS. DETERMINE EXACT STALLATION OF ELECTRICAL WIRING WITH CONDITIONS OF	\boxtimes	CONTACTOR
CONSTRUCTIO		60	CIRCUIT BREAKER
	GH-IN, COORDINATE EXACT LOCATIONS OF ALL DEVICES AND	VFD	VARIABLE FREQUENCY DRIVE
	TH ARCHITECTURAL ELEVATIONS, MILLWORK, REFLECTED AND MECHANICAL EQUIPMENT.		EXISTING PANELBOARD, SURFACE MOUNTED
	S SHALL NOT BE MOUNTED BACK TO BACK. MAINTAIN MINIMUM		EXISTING PANELBOARD, FLUSH MOUNTED
LATERAL SEPA	RATIONS OF 24".		PANELBOARD, SURFACE MOUNTED
			, and the second se
ALL EXISTING	CONDITIONS ARE NOT SHOWN ON THE DRAWINGS. SHALL CAREFULLY EXAMINE THE EXISTING SITE AND BECOME		DANELBUADD ELLICH MULINTED
ALL EXISTING (CONTRACTOR FAMILIAR WITH			PANELBOARD, FLUSH MOUNTED TRANSFORMER, DRY-TYPE
ALL EXISTING (CONTRACTOR FAMILIAR WITH ALLOWED DUE THE EXACT LO WITH STRUCTU	SHALL CAREFULLY EXAMINE THE EXISTING SITE AND BECOME THE EXISTING CONDITIONS. NO ADDITIONAL CHARGES WILL BE TO THE LACK OF PRE-BID SITE EXAMINATION. CATION OF ELECTRICAL EQUIPMENT SHALL BE COORDINATED JRE AND MECHANICAL EQUIPMENT. ADJUST EQUIPMENT		
ALL EXISTING (CONTRACTOR FAMILIAR WITH ALLOWED DUE THE EXACT LO WITH STRUCTL LOCATION AS F	SHALL CAREFULLY EXAMINE THE EXISTING SITE AND BECOME THE EXISTING CONDITIONS. NO ADDITIONAL CHARGES WILL BE TO THE LACK OF PRE-BID SITE EXAMINATION. CATION OF ELECTRICAL EQUIPMENT SHALL BE COORDINATED JRE AND MECHANICAL EQUIPMENT. ADJUST EQUIPMENT REQUIRED TO MAINTAIN NEC WORKING CLEARANCES.		TRANSFORMER, DRY-TYPE
ALL EXISTING OF CONTRACTOR FAMILIAR WITH ALLOWED DUE THE EXACT LOWITH STRUCTUL LOCATION AS FALL SPARE COCONDUIT SHALL	SHALL CAREFULLY EXAMINE THE EXISTING SITE AND BECOME THE EXISTING CONDITIONS. NO ADDITIONAL CHARGES WILL BE TO THE LACK OF PRE-BID SITE EXAMINATION. CATION OF ELECTRICAL EQUIPMENT SHALL BE COORDINATED JRE AND MECHANICAL EQUIPMENT. ADJUST EQUIPMENT	₩ □ 4 RC	TRANSFORMER, DRY-TYPE TRANSFORMER, PAD MOUNTED ELECTRIC METER, BUILDING MOUNTED ROOM CONTROLLER
ALL EXISTING OF CONTRACTOR FAMILIAR WITH ALLOWED DUE THE EXACT LOWITH STRUCTUL LOCATION AS FALL SPARE COCONDUIT SHALL OPPOSITE END COORDINATE EWITH POWER OF CONTRACTOR CONTRA	SHALL CAREFULLY EXAMINE THE EXISTING SITE AND BECOME THE EXISTING CONDITIONS. NO ADDITIONAL CHARGES WILL BE TO THE LACK OF PRE-BID SITE EXAMINATION. CATION OF ELECTRICAL EQUIPMENT SHALL BE COORDINATED JRE AND MECHANICAL EQUIPMENT. ADJUST EQUIPMENT REQUIRED TO MAINTAIN NEC WORKING CLEARANCES. NDUIT SHALL CONTAIN A PULL CORD. EACH END OF THE L HAVE A LABEL IDENTIFYING THE TERMINATION POINT OF THE	T Q RC XXX.X	TRANSFORMER, DRY-TYPE TRANSFORMER, PAD MOUNTED ELECTRIC METER, BUILDING MOUNTED
ALL EXISTING OCONTRACTOR FAMILIAR WITH ALLOWED DUE THE EXACT LO WITH STRUCTUL LOCATION AS FALL SPARE CO CONDUIT SHALL OPPOSITE END COORDINATE E WITH POWER OF THAT THEY AR CONTRACTOR UTILITIES PRIORITIAN CONTRACTOR CONTRA	SHALL CAREFULLY EXAMINE THE EXISTING SITE AND BECOME THE EXISTING CONDITIONS. NO ADDITIONAL CHARGES WILL BE TO THE LACK OF PRE-BID SITE EXAMINATION. CATION OF ELECTRICAL EQUIPMENT SHALL BE COORDINATED JRE AND MECHANICAL EQUIPMENT. ADJUST EQUIPMENT REQUIRED TO MAINTAIN NEC WORKING CLEARANCES. NDUIT SHALL CONTAIN A PULL CORD. EACH END OF THE JL HAVE A LABEL IDENTIFYING THE TERMINATION POINT OF THE OF THE CONDUIT. EXACT LOCATION OF ALL WALL MOUNTED VOICE/DATA OUTLETS DUTLETS. ADJUST LOCATION OF ALL VOICE DATA OUTLETS SO	T Q RC XXX.X	TRANSFORMER, DRY-TYPE TRANSFORMER, PAD MOUNTED ELECTRIC METER, BUILDING MOUNTED ROOM CONTROLLER
ALL EXISTING OF CONTRACTOR FAMILIAR WITH ALLOWED DUE THE EXACT LOWITH STRUCTUL LOCATION AS FALL SPARE COCONDUIT SHALL OPPOSITE END COORDINATE EWITH POWER OF THAT THEY AR CONTRACTOR UTILITIES PRIOUSHALL BE REPARLL CIRCUITS STANDED TO THE STANDED T	SHALL CAREFULLY EXAMINE THE EXISTING SITE AND BECOME THE EXISTING CONDITIONS. NO ADDITIONAL CHARGES WILL BE TO THE LACK OF PRE-BID SITE EXAMINATION. CATION OF ELECTRICAL EQUIPMENT SHALL BE COORDINATED JIRE AND MECHANICAL EQUIPMENT. ADJUST EQUIPMENT REQUIRED TO MAINTAIN NEC WORKING CLEARANCES. NDUIT SHALL CONTAIN A PULL CORD. EACH END OF THE JL HAVE A LABEL IDENTIFYING THE TERMINATION POINT OF THE OF THE CONDUIT. EXACT LOCATION OF ALL WALL MOUNTED VOICE/DATA OUTLETS DUTLETS. ADJUST LOCATION OF ALL VOICE DATA OUTLETS SO E LOCATED AT THE SAME ELEV. AND OFFSET HORIZONTALLY 6". IS RESPONSIBLE FOR LOCATING ALL EXISTING UNDERGROUND R TO EXCAVATION. ANY DAMAGE TO THE EXISTING UTILITIES	T Q RC XXX.X	TRANSFORMER, DRY-TYPE TRANSFORMER, PAD MOUNTED ELECTRIC METER, BUILDING MOUNTED ROOM CONTROLLER

12. CONTRACTOR IS RESPONSIBLE FOR ALL TRENCHING, PATCHING, EXCAVATION, BACKFILL AND RESTORATION RELATED TO THEIR WORK.



Revision	Date	Ву
Final	4/2/25	AB
Re-Scope	5/7/25	AB

Re-Scope 1:1 S.Galli A.Bronec, P.E. A.Bronec, P.E. A.Bronec, P.E.



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Cushing Terrell

306 Railroad St. Missoula, MT 59802 Phone (406) 544-8565

City Of Missoula

Garden City Compost Facility [Improvements]

SCHEDULES AND **LEGEND**


FUTURE CURING DATA RACK HANDLING BUILDING EXISTING DRYING BEDS COMPOSTING BAYS (TYP. OF 12) TO FIBER PATCH PANEL TO MDP RUNOFF LIFT STATION. PUMPS TO DRYING BED DRAIN COMPOST FAN (TYP OF 12) CONTROL BUILDING SEE E3 BIO FAN 102 SEE E-4 FOR ENLARGED SITE PLAN BIO FAN

OVERALL ELECTRICAL SITE PLAN

1" = 40'-0"

KEY NOTES

- 1. 4" CONDUIT FOR FEEDER FROM MSB-A TO MDP. SEE ONE-LINE DIAGRAM E-2.
- 3" CONDUIT WITH FIBER FROM PLC IN CONTROL BUILDING TO DATA RACK IN SOLIDS HANDLING BUILDING.
- 3. LIFT STATION FEEDER TO MDP. SEE ONE-LINE DIAGRAM E-2.
- 4. NOT USED
- 5. PROVIDE (1) 3" SPARE CONDUIT WITH PULL CORD.
- 6. STUB UP AND CAP SPARE CONDUIT 1 FT ABOVE GRADE.



Revision	Date	Ву
Final	4/2/25	AB
Re-Scope	5/7/25	AB

Revision
Re-Scope
Plot Scale

S.Galli proved By

A.Bronec, P.E.

necked By
A.Bronec, P.E.

esigned By
A.Bronec, P.E.

Engineer



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Cushing Terrell

306 Railroad St. Missoula, MT 59802 Phone (406) 544-8565

Owner

City Of Missoula


Project T


Garden City
Compost
Facility
Improvements


Sneet 11t


OVERALL ELECTRICAL SITE PLAN

Sheet
















- 1. ROUTE NEW FEEDER IN EXISTING SPARE CONDUIT.
- 2. ENCLOSED CIRCUIT BREAKER SHALL BE 400A/3P/480V, 14K AIC, NEMA 3R ENCLOSURE, MOUNT ADJACENT TO MSB-6.
- 3. EXISTING SPARE CONDUIT STUBS UP INSIDE MSB-6. EXTEND CONDUIT TO NEW 400A CIRCUIT BREAKER. PROVIDE NEW CONDUIT/CONDUCTORS BETWEEN 400A CIRCUIT BREAKER AND PANEL MDP.
- 4. DO NOT BOND N-G TOGETHER. PROVIDE NEC GROUNDING AS FOLLOWS: • (2) 3/4" X 8' COPPER CLAD DRIVEN RODS. CONNECT WITH #4 CU.
- 20 FT LONG #4 CU IN FOOTING OF CONTROL BUILDING FOUNDATION. (UFER GROUND).
- #4 CU BOND TO CONTROL BUILDING STEEL.
- #4 CU BOND TO ANTENA MAST.
- NOT USED

-(N) 400A/480V/3P

2


400.4

"MDP"

480/277V

CIRCUIT BREAKER

6. DATA RACK SHALL BE WALL MOUNTED RACK WITH CAT 6 PATCH PANEL AND FIBER PATCH PANEL. ETHERNET SWITCH TO BE PROVIDED BY CITY.



willing.							
Revision	Date	Ву					
Final	4/2/25	AB					
Re-Scope	5/7/25	AB					

Re-Scope	5/7/25	AB				
Revision						
Re-Scope						

Ke-Scope		
Plot Scale		
1:1		
Drawn By		
S.Galli		
Approved By A.Bronec, P.E.		
Checked By A.Bronec, P.E.		
Designed By A.Bronec, P.E.		



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303


Cushing Terrell

306 Railroad St. Missoula, MT 59802 Phone (406) 544-8565

City Of Missoula

Garden City Compost Facility Improvements

ONE-LINE DIAGRAM





- NOT USED
- NOT USED
- NOT USED
- NOT USED
- 5. PROVIDE ANTENA MAST CONSISTING OF 1.5" RIGID STEEL CONDUIT TERMINATED 10 FT ABOVE CONTROL BUILDING.
- 6. 1"C, (4) STRAND 50/125 MICRON, SM, CABLE TO DATA CABINET.
- 8. 120V CONTROL POWER. SEE ONE-LINE FOR 480V FEEDER.
- 9. WALL LIGHT WITH PHOTO CELL AND MOTION SENSOR.
- NOT USED
- 11. NOT USED
- 12. NOT USED
- 13. NOT USED
- 14. NOT USED
- 15. PROVIDE CONNECTION TO EXHAUST FAN AND LINE VOLTAGE REVERSE ACTING



377111111				
Revision	Date	Ву		
Final	4/2/25	AB		
Re-Scope	5/7/25	AB		

Re-Scope 1:1

S.Galli A.Bronec, P.E.

A.Bronec, P.E. A.Bronec, P.E.



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Cushing Terrell

306 Railroad St. Missoula, MT 59802 Phone (406) 544-8565

City Of Missoula

Garden City Compost Facility Improvements

CONTROL BUILDING ELECTRICAI **PLANS**

COMPOST FAN (TYP OF 12) ——/ CONTROL BUILDING SEE E-3 BIO-FAN COMPOST AND BIOFILTER ELECTRICAL PLAN SCALE: 1/16" = 1'-0"



- 1"C WITH 3#10, 1#10 GND SHIELDED VFD CABLES PLUS 2 #14 SHIELD CONTROL CABLE FOR VFD SHUT DOWN SIGNAL. ROUTE TO BAY 1-6 DRIVE CABINET.
- 2. 1"C WITH 3#10, 1#10 GND SHIELDED VFD CABLES PLUS 2 #14 SHIELD CONTROL CABLE FOR VFD SHUT DOWN SIGNAL. ROUTE TO BAY 7-12 DRIVE CABINET.
- 3. 1-1/2"C WITH 3#2, 1#8 GND SHIELDED VFD CABLES PLUS 2 #14 SHIELD CONTROL CABLE FOR VFD SHUT DOWN SIGNAL. ROUTE TO BIOFILTER DRIVE CABINET.
- 4. NOT USE
- 5. TO WELL PUMP CONTROLLER. SEE ONE-LINE DIAGRAM E-1 FOR FEEDER.
- 6. NOT USED
- 7. PROVIDE 30A / 3P / NF / NEMA 3R DISCONNECT SWITCH AT EACH COMPOST FAN.
 DISCONNECT SWITCH SHALL INCLUDE EARLY BREAK CONTACTS FOR VFD SHUTDOWN.
- 8. PROVIDE 100A / 3P / NF / NEMA 3R DISCONNECT SWITCH AT EACH COMPOST FAN. DISCONNECT SWITCH SHALL INCLUDE EARLY BREAK CONTACTS FOR VFD SHUTDOWN.
- 9. PRESSURE AND TEMP TRANSMITTER.
- 10. 1"C WITH PRESSURE AND TEMP TRANSMITTER WIRING.

ALAN BRONEC 11707 PE

	·/////////					
	Revision	Date	Ву			
	Final	4/2/25	AB			
	Re-Scope	5/16/25	AB			

Revision Re-Scope

1:1

S.Galli

A.Bronec, P.E.
Checked By
A.Bronec, P.E.

Designed By
A.Bronec, P.E.

Engineer



1064 N. Warren Helena, MT 59601 Phone (406) 449-3303

Cushing Terrell

306 Railroad St. Missoula, MT 59802 Phone (406) 544-8565

Owner

City Of Missoula

roject Titl

Garden City
Compost
Facility
Improvements

heet Title

COMPOST AND BIOFILTER ELECTRICAL PLAN

Sheet